



WORK GEAR



NITRILE GLOVES

GRAY 600mm / 24in



8
mil

ULTRA TOUGH - LONG CUFF DISPOSABLE GLOVES
AMERICA'S ONLY 24 INCH XTREME REACH GRAY NITRILE GLOVE

TGC® GRAY GLOVE FEATURES

Disposable Gloves That Protect Your Hand & Forearm

Xtreme Reach 600mm/ 24in Cuff - Upper Forearm Protection



- Superior Chemical Resistance
- Excellent Puncture Resistance
- Hand & Forearm Protection
- Fitted Long Beaded Cuff
- Minimise Moisture Entering Glove
- 100% Nitrile
- Latex Free - Vinyl Free - MBT Free

TGC WorkGear Gloves Withstand:

Strong Cleaners	Diesel
Acids	Hydraulic Fluids
Alkalies	Oils
Solvents	Paint Thinner
Biohazards	Petrol

140+ ratings on other Chemicals!



These Super Tough Gloves are Perfect for:

- Repair & Maintenance Industries
- Plumbing
- Aircraft Fitting & Maintenance
- Diesel Repair & Maintenance
- Fuelling & Oil Dispensing
- Laboratory Work
- Materials Handling
- Chemical Processing

CHEMICAL RESISTANCE GUIDE



Key

E Excellent Chemical Resistance

G Good Chemical Resistance

F Fair Chemical Resistance

P Poor Chemical Resistance

CHEMICAL NAME	NITRILE	CHEMICAL NAME	NITRILE	CHEMICAL NAME	NITRILE	CHEMICAL NAME	NITRILE
Acetaldehyde	P	Diallylamine	P	Hydrofluoric Acid, <50%	E	Pentane	E
Acetic Acid	G	Dichloroacetyl Chloride	P	Isobutyl alcohol	E	Perchloric Acid, 30-70%	E
Acetic Anhydride	F	Diesel Fuel	E	Isooctane	E	Perchloroethylene	G
Acetone	F	Diethanolamine	E	Isopropyl Alcohol	E	Peroxyacetic Acid	P
Acetonitrile	F	Diethylamine	G	Isopropylamine	P	Petroleum Ethers, 80-11 OC	G
Acrylic Acid	G	Die Thylene Glycol	E	Jet Fuel, <30% Aromatics 73-248C	G	Phenol, >70%	E
Ammonium Acetate	E	Die Thylene Triamine	P	Kerosene	E	Phosphoric Acid, >70%	E
Ammonium Carbonate	E	Diisobutylketone	G	Lactic Acid	E	Picric Acid	E
Ammonium Flouride 30-70%	E	Diisobutylamine	E	Lauric Acid	G	Potassium Hydroxide	E
Ammonium Hydroxide <70%	E	Dime Thyl Ether	G	Malathion, 30-70%	E	Potassium Iodide	E
Amyl Alcohol	E	Dime Thyl Sulfoxide (DMSOC)	G	Methanol	F	Propylacetate	F
Aniline	F	Dime Thylace Tamide	F	Methyl Acetate	P	Pyridine	P
Aqua Regia	P	Dimethylformamide (DMF)	P	Methyl Ethyl Ketone	P	Silicon Etch	G
Benzaldehyde	P	1,3-Dioxane	P	Methyl Isobutyle Ketone	P	Silver Nitrate	G
Benzene	G	1,4-Dioxane	P	Methyl Methacrylate	P	Sodium Carbonate	E
Boric Acid	E	Epichlorohydrin	P	Methylene Chloride	P	Sodium Chloride	E
Bromopropionic Acid	F	Ethanol	E	N-Amylacetate	F	Sodium Flouride	E
Butylacrylate	P	Ethylacetate	P	N-Butylacetate	F	Sodium Hydroxide, 30-70%	E
ButylCellusolve	G	Ethylether	G	N-Butyl Alcohol	E	Sodium Hypochlorite	E
Calcium Hydroxide	E	Ethylene Glycol Dimethylether	F	N-Methyl-2-Pyrrolidone	P	Sodium Thiosulfate	E
Carbon Disulfide	G	Ethylene Dichloride	P	N-Nitrosodie Thylamine	P	Styrene	P
Carbon Tetrachloride	P	Ethylene Glycol	E	N-Propyl Alcohol	E	Sulfuric Acid, 30-70%	F
Chlorobenzene	P	Formaldehyde, 30-70%	E	Naphtha, 15-20% Aromatics	E	Sulfuric Acid, <30%	G
Chlorodibromomethane	P	Formic Acid	G	Naphta, <3% Aromatics	E	Sulfuric Acid, >70%	P
Chloroform	P	Freon 113 OR TF	E	Nitric Acid, <30%	E	Tannic Acid	G
Chloronaphthalenes	P	Freon TMC	F	Nitric Acid, 30-70%	P	1,2,4,5-Tetrachlorobenzene	E
Chromic Acid	F	Furfural	P	Nitrobenzene	F	1,1,1,2-Tetrachloroethane	F
Cisplatin	G	Gasoline, Petrol, 40-50% Aromatics	E	Nitroethane	P	Tetrahydrofuran	F
Citric Acid 30-70%	G	Gasoline, Unleaded Petrol	G	1-Nitropropane	P	Toluene	F
Cyclohexane	E	Glutaraldehyde, <5%	G	Octane	E	Toluene -2,4-Diisocyanate (TDI)	P
Cyclohexanol	E	Glycerol	E	Octylalcohol	E	1,2,4-Trichlorobenzene	F
Cyclohexanone	P	Heptanes	E	Oleic Acid	E	1,1,1-Trichloroethane	P
Cyclohexylamine	P	Hesmethyldisiloxane	G	Oxalic Acid	E	Trichloroethylene	P
Di-N-Amylamine	E	Hexane	E	Palmitic Acid	E	Tricresylphosphate	G
Di-N-Butylamine	E	Hydrazine	E	PCB (Polychlorinated Biphenyls)	G	Turpentine	E
Di-N-Butylphthalate	E	Hydrochloric Acid, <30%	G	Pentachlorophenol	G	Xylenes	F
Di-N-Octylphthalate	E	Hydrochloric Acid, 30 -70%	G				
Diaze Tone Alcohol	G						

The chemical resistance information on this chart is intended to provide general information about the reaction of Nitrile examination glove films to the commonly used chemicals listed.

The rating scale takes into consideration three primary factors:

- 1) The ability of the chemical to permeate (pass through) the glove film;
- 2) The ability of the chemical to degrade (break down) the physical structure of the glove film;
- 3) The risk that contact exposure to the chemical poses to the glove wearer.

TGC WorkGear Nitrile Gloves are thin gauge disposable products designed to provide a barrier protection and tactile sensitivity to the wearer. Our gloves are not designed for applications involving prolonged, direct exposure to chemicals. Our intent in providing this chemical compatibility information is to provide a guideline for the use of our gloves in applications where incidental splash exposure to various chemicals may occur.

TGC WorkGear recommend you USE CAUTION AT ALL TIMES.

Verify that your gloves are compatible with your specific applications, processes and materials before using. When performing processes where gloves will receive prolonged, direct exposure to chemicals, use a glove specifically designed for chemical handling. Avoid the risk of exposing your workers, products and facilities to chemical cross contamination: immediately dispose of gloves after contact with chemicals. Double gloving provides additional barrier protection and allows the outer glove to be disposed of after contact with chemicals without exposing the hand.

June/23/2016

TGC[®] NITRILE GLOVES

GRAY 600mm/24in

WORK GEAR



TGC Grey 600mm/24in - Xtreme Reach Cuff
12 gloves per box

NSN Numbered

Size	Part No.	NSN No.
Medium	162602	8415-66-161-9918
Large	162603	8415-66-161-9919
X-Large	162604	8415-66-161-9920
XX-Large	162605	8415-66-161-9921

Certified to

TGC WorkGear Nitrile Gloves are manufactured in an ISO 9001 certified facility.

EN Standard for medical gloves for single use and requirements tested for physical properties in accordance with EN 455 Part 1, 2, 3, 4.



For Single Use
Non-Sterile

www.theGloveCompany.com

MADE IN MALAYSIA

