



Revision Number: 004.0

Issue date: 07/03/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	H8000 SPEEDBONDR PART A 5GA PA	IDH number:	392457
Product type:	Acrylics	Item number:	35939
		Region:	United States
Company address:		Contact information:	
Henkel Corporation		Telephone: 860.571.5100	
One Henkel Way		MEDICAL EMERGENCY Phone: Poison Control Center	
Rocky Hill, Connecticut 06067		1-877-671-4608 (toll free) or 1-303-592-1711	
		TRANSPORT EMERGENCY Phone: CHEMTREC	
		1-800-424-9300 (toll free) or 1-703-527-3887	
		Internet: www.henkelna.com	

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state:	Liquid	HEALTH:	*2
Color:	Yellow, Opaque	FLAMMABILITY:	3
Odor:	Sharp	PHYSICAL HAZARD:	1
		Personal Protection:	See MSDS Section 8

WARNING: FLAMMABLE LIQUID AND VAPOR.
CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
MAY CAUSE ALLERGIC SKIN REACTION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation:	Causes respiratory tract irritation. Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Methyl methacrylate	80-62-6	30 - 60
Methacrylate ester	Proprietary	10 - 30
Methacrylic acid	79-41-4	5 - 10
Synthetic rubber	Proprietary	5 - 10
Methacrylate ester	Proprietary	1 - 5
Talc	14807-96-6	0.1 - 1
Polyvinyl chloride	9002-86-2	0.1 - 1

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	14 °C (57.2 °F) Setaflash Closed Cup
Autoignition temperature:	Not available.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Hydrogen chloride. Hydrogen cyanide. Styrene. Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material. Keep container closed.
------------------	--

Storage:

For safe storage, store at or below 32 °C (89.6 °F)
 Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Protect from direct sunlight. Maintain head space in storage containers to support oxygen requirements of the inhibitor(s).

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methyl methacrylate	50 ppm TWA 100 ppm STEL (Sensitiser.)	100 ppm (410 mg/m ³) TWA	None	50 ppm
Methacrylate ester	None	None	None	None
Methacrylic acid	20 ppm TWA	None	None	None
Synthetic rubber	None	None	None	None
Methacrylate ester	None	None	None	None
Talc	2 mg/m ³ TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable. 0.3 mg/m ³ TWA Total dust.	None	50 ppm
Polyvinyl chloride	1 mg/m ³ TWA Respirable fraction.	5 mg/m ³ TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m ³ TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Liquid

Color:

Yellow, Opaque

Odor:

Sharp

Odor threshold:

Not available.

pH:

Not available.

Vapor pressure:

Not available.

Boiling point/range:

> 100 °C (> 212°F)

Melting point/ range:

Not available.

Specific gravity:

0.94

Vapor density:

> 1

Flash point:

14 °C (57.2 °F) Setaflash Closed Cup

Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	Faster than ether., (Ether = 1)
Solubility in water:	Soluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	1.37 %; 12.87 g/l (Adhesive and Activator mixed)

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Polymerization may occur at elevated temperatures or upon depletion of inhibitor.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Hydrogen chloride. Hydrogen cyanide. Styrene. Toxic fumes. Irritating vapors.
Incompatible materials:	Oxidizing agents. Reducing agents. Acids. Bases. Peroxides.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials. Do not mix in batches greater than 100 grams (0.22 pounds) unless you plan to use immediately. Protect from direct sunlight. Loss of polymerization inhibitor. Loss of dissolved air. Inert gas blanketing.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methyl methacrylate	No	No	No
Methacrylate ester	No	No	No
Methacrylic acid	No	No	No
Synthetic rubber	No	No	No
Methacrylate ester	No	No	No
Talc	No	No	No
Polyvinyl chloride	No	No	Yes

Hazardous components	Health Effects/Target Organs
Methyl methacrylate	Allergen, Irritant, Kidney, Liver, Mutagen, Nervous System, Respiratory
Methacrylate ester	Irritant, Allergen
Methacrylic acid	Corrosive, Irritant, Allergen
Synthetic rubber	No Target Organs
Methacrylate ester	Irritant, Allergen
Talc	Irritant, Lung, Some evidence of carcinogenicity
Polyvinyl chloride	Respiratory

12. ECOLOGICAL INFORMATION

Ecological information:	Not available.
--------------------------------	----------------

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II
DOT Reportable quantity: Methyl methacrylate

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: Fire, Immediate Health, Delayed Health
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methyl methacrylate (CAS# 80-62-6).

CERCLA Reportable quantity: Methyl methacrylate (CAS# 80-62-6) 1,000 lbs. (454 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

WHMIS hazard class: B.2, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 15

Prepared by: Rena Petrides, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.