



Revision Date: 01/15/2007

Issue date: 01/15/2007

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product name:** HYSOL 1942 POLYSHOT 35 LB CT  
**Product type:** Industrial Hot Melt Adhesive  
**Company address:**  
Henkel Corporation  
1001 Trout Brook Crossing  
Rocky Hill, Connecticut 06067

**Item No. :** 83277  
**Region:** United States  
**Contact Information:**  
Telephone: 860.571.5100  
Emergency telephone: 860.571.5100  
Internet: www.loctite.com

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Rosin ester 8050-26-8	10-30	None	None	None
Rosin 8050-09-7	10-30	None	None	None
Rosin, polymerized 65997-05-9	5-10	None	None	None
Paraffin wax 8002-74-2	1-5	2 mg/m <sup>3</sup> TWA	None	None

Non hazardous components  
EVA Hotmelt Adhesive

### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

HMIS:

<b>Physical state:</b> Solid	<b>HEALTH:</b>	1
<b>Color:</b> Off-white	<b>FLAMMABILITY:</b>	0
<b>Odor:</b> Slight	<b>PHYSICAL HAZARD:</b>	0
	<b>Personal Protection:</b>	See Section 8

**WARNING:** MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.  
Dust from talc may cause irritation or allergic reaction

**Relevant routes of exposure:** Molten adhesive, Skin, Eyes, Solid adhesive has no hazards

#### Potential Health Effects

**Inhalation:** Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts from solid adhesive may cause irritation.  
**Skin contact:** Molten adhesive may cause severe burns. Solid adhesive has no hazards  
**Eye contact:** Molten adhesive in eyes will cause severe and permanent damage. Can cause mechanical irritation if dusts are generated.  
**Ingestion:** Not expected to be harmful by ingestion.

**Existing conditions aggravated by exposure:** None known

See Section 11 for additional toxicological information.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.
<b>Skin contact:</b>	Thermal burn hazard from molten adhesive. Cool melted product on skin with plenty of water. Do not remove solidified product. Cover affected areas with clean sheeting or gauze and seek immediate medical attention. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn.
<b>Eye contact:</b>	If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.
<b>Ingestion:</b>	Ingestion of solid adhesive is not expected to be hazardous. Get medical attention if symptoms develop and persist.

#### 5. FIRE-FIGHTING MEASURES

<b>Flash point:</b>	Greater than 232°C (450°F)
<b>Autoignition temperature:</b>	Not applicable
<b>Flammable/Explosive limits-lower %:</b>	Not applicable
<b>Flammable/Explosive limits-upper %:</b>	Not applicable
<b>Extinguishing media:</b>	Use extinguishing measures appropriate to local circumstances and the surrounding environment. Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special fire fighting procedures:</b>	None
<b>Unusual fire or explosion hazards:</b>	None
<b>Hazardous combustion products:</b>	Oxides of carbon. Acrid smoke and fumes.

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Environmental precautions:</b>	No special environmental precautions required. Do not allow material to contaminate ground water system.
<b>Clean-up methods:</b>	Health injuries are not known or expected under normal use. Sweep up spilled material. Avoid creating dust.

#### 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid contact with molten material. Always be careful around molten material. Do not place wet or damp solid into melt tank. Follow suggested application temperature. Do not wear contact lenses.
<b>Storage:</b>	Do not store above 38°C (100°F).
<b>Incompatible products:</b>	No special restrictions on storage with other products.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Engineering controls:</b>	Ventilation hoods and fans required when working with organic solvents or in hot melt applications. Heat only in areas with appropriate exhaust ventilation.
------------------------------	--

Item No. : 83277

Product name: HYSOL 1942 POLYSHOT 35 LB CT

**Respiratory protection:** Respirator with combination filter for vapour/particulate. In case of insufficient ventilation wear suitable respiratory equipment.

**Skin protection:** Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses when handling this product.

See Section 2 for exposure limits.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Solid  
**Color:** Off-white  
**Odor:** Slight  
**Vapor pressure:** Not applicable  
**pH:** Not applicable  
**Boiling point/range:** Not available  
**Melting point/range:** 110.2°C (230°F)  
**Specific gravity:** 0.94  
**Vapor density:** Not available  
**Evaporation rate:** Not applicable  
**Solubility in water:** Insoluble.  
**Partition coefficient (n-octanol/water):** Not available  
**VOC content:** Zero

## 10. STABILITY AND REACTIVITY

**Stability:** Stable.

**Hazardous polymerization:** Will not occur.

**Hazardous decomposition products:** None under normal use.

**Incompatibility:** Avoid heating above 400 Degrees F

**Conditions to avoid:** Prolonged heating at temperatures above 200 °C.

## 11. TOXICOLOGICAL INFORMATION

**Product toxicity data:** Loctite is not aware of any toxicity data on the specific mixture of chemical components contained in this product.

### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Rosin ester 8050-26-8	No	No	No
Rosin 8050-09-7	No	No	No
Rosin, polymerized 65997-05-9	No	No	No
Paraffin wax 8002-74-2	No	No	No

### Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Rosin ester 8050-26-8	Irritant
Rosin 8050-09-7	Respiratory, Irritant, Allergen
Rosin, polymerized 65997-05-9	No Records
Paraffin wax 8002-74-2	Irritant

## 12. ECOLOGICAL INFORMATION

**Ecological information:**

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, groundwater, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of in accordance with Federal, State and local regulations.

**EPA hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

**U.S. Department of Transportation Ground (49 CFR):**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**International Air Transportation (ICAO/IATA):**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**WaterTransportation (IMO/IMDG):**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None  
**Exceptions:** None  
**Marine pollutant:** None known

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12 (b) Export Notification:** None.

**CERCLA/SARA Section 302 EHS:** None above reporting de minimus.  
**CERCLA/SARA Section 311/312:** Immediate Health Hazard  
**CERCLA/SARA 313:** None.

**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Domestic Substances List.  
**WHMIS hazard class:** D.2.B

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

**Prepared by:** Lou Fabrizio, Senior Health & Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.