

Material Safety Data Sheet



Revision Number: 002.1

Issue date: 05/05/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Pipe Repair Kit EPOXY STICK
Product type: Epoxy stick
Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

IDH number: 702201
Item number: 96322_314111
Region: United States
Contact information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Putty
Color: Metallic, Black
Odor: Mercaptan, Sulfur

HMIS:
HEALTH: *1
FLAMMABILITY: 1
PHYSICAL HAZARD: 0
Personal Protection: See MSDS Section 8

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.
MAY CAUSE EYE AND SKIN IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation: Contains crystalline silica (quartz), which is classified as a possible carcinogen. However, the crystalline silica present in this product is encapsulated in the liquid and will only be liberated if the product is sanded or abraded, and even then what is liberated will not be pure crystalline silica. Appropriate precautions, however, should be taken if the product is sanded or abraded to prevent personnel from breathing the dust.

Skin contact: Causes skin irritation. May cause allergic skin reaction.

Eye contact: Contact with eyes will cause irritation.

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Existing conditions aggravated by exposure: Eye, skin and respiratory disorders. Skin allergies.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Talc	14807-96-6	30 - 60
Iron	7439-89-6	10 - 30
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	10 - 30
Glass, oxide, chemicals	65997-17-3	10 - 30
Polyether polymercaptan	Unknown	5 - 10
Quartz (SiO ₂)	14808-60-7	5 - 10
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	5 - 10
Treated fumed silica	67762-90-7	1 - 5

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Keep individual calm. Never give anything by mouth to an unconscious person. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	Not applicable
Autoignition temperature:	Not applicable
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Aldehydes. Acids. Oxides of carbon. Oxides of nitrogen. Oxides of sulfur.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Store in a partly filled, closed container until disposal. Scrape up as much material as possible.

7. HANDLING AND STORAGE

Handling:	Avoid skin and eye contact. Wash thoroughly after handling. Empty container precaution: Attention! This container can be hazardous when empty. Follow label cautions even after the container is empty since empty containers could retain product residues. Do not re-use empty containers for food, clothing, or products for human or animal consumption, or where skin contact can occur.
Storage:	For safe storage, store at or below 32 °C (89.6 °F) Keep in a cool, well ventilated area.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Talc	2 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	50 ppm
Iron	None	None	None	None
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Glass, oxide, chemicals	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	None	None	None
Polyether polymercaptan	None	None	None	None
Quartz (SiO ₂)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None
2,4,6-Tris(dimethylaminomethyl)phenol	None	None	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None

Engineering controls:

Use local exhaust ventilation if heated above 38°C (100°F) to maintain concentrations below occupational exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Putty
Color:	Metallic, Black
Odor:	Mercaptan, Sulfur
Odor threshold:	Not available
pH:	Not applicable
Vapor pressure:	Not determined
Boiling point/range:	Not available
Melting point/ range:	Not applicable
Specific gravity:	2.18
Vapor density:	Not applicable
Flash point:	Not applicable
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Evaporation rate:	Not applicable
Solubility in water:	Not miscible
Partition coefficient (n-octanol/water):	Not available
VOC content:	< 1 %

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Aldehydes. Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Acids.
Incompatible materials:	None
Conditions to avoid:	None known

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Talc	No	No	No
Iron	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Glass, oxide, chemicals	No	No	No
Polyether polymercaptan	No	No	No
Quartz (SiO ₂)	Known carcinogen.	Group 1	No
2,4,6-Tris(dimethylaminomethyl)phenol	No	No	No
Treated fumed silica	No	No	No

Hazardous components	Health Effects/Target Organs
Talc	Irritant, Lung, Some evidence of carcinogenicity
Iron	Eyes, Lung
Epichlorohydrin-4,4'-isopropylidene diphenol resin	Allergen, Irritant
Glass, oxide, chemicals	Allergen, Respiratory
Polyether polymercaptan	No Data
Quartz (SiO ₂)	Immune system, Lung, Some evidence of carcinogenicity
2,4,6-Tris(dimethylaminomethyl)phenol	Irritant, Allergen
Treated fumed silica	Irritant

12. ECOLOGICAL INFORMATION

Ecological information:	Not applicable
--------------------------------	----------------

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Follow all local, state, federal and provincial regulations for disposal.
Hazardous waste number:	Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification:	None above reporting de minimus
CERCLA/SARA Section 302 EHS:	None above reporting de minimus
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA 313:	None above reporting de minimus
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
WHMIS hazard class:	D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Gary Pierson, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.