



**LPS LABORATORIES**  
**U.S. MATERIAL SAFETY DATA SHEET**  
**LPS HardCoat Corrosion Inhibitor Bulk**

---

**Section 1 • Product and Company Identification**

---

**Manufacturer's Name:** LPS Laboratories

**Part Number:** 03328,03305,03355

**Trade Name:** LPS HardCoat Corrosion Inhibitor

**Chemical Family:** Petroleum Hydrocarbons

**Address:**

4647 Hugh Howell Road  
Tucker, GA USA 30085-5052

Telephone Number: 770-243-8800

Emergency Telephone Number: 1-800-424-9300 Chemtrec;  
Outside U.S.: (703) 527-3887

---

**PLAIN LANGUAGE HAZARD SUMMARY**

---

Material Safety Data Sheets can be confusing. Federal and State laws require us to include a great deal of technical information that probably won't help the non-professional. LPS includes this "PLAIN LANGUAGE HAZARD SUMMARY" to address the questions and concerns of the average worker. If you have additional health, safety or product questions, don't hesitate to call us at 800/241-8334.

**Worker Toxicity**

LPS HARDCOAT CORROSION INHIBITOR is an industrial chemical. It is a specialized coating designed to prevent rust and corrosion on steel, aluminum and other metals. It contains "mineral spirits" and mineral oil which can be irritating to skin at a minimum and if handled improperly can be dangerous. We suggest you wear gloves and avoid extended exposure to unprotected skin. Don't get it in your eyes (it stings), or breath large amounts of the vapor, (it will dry out your nasal passages and if you breathe large amounts in poorly ventilated areas it can make you dizzy and even sick). Don't spray LPS HARDCOAT CORROSION INHIBITOR for extended periods without adequate ventilation. If you're going to perform work involving a lot of product in a poorly ventilated area, use of a respirator or self-contained breathing equipment may be required. For more exposure and first aid information, refer to MSDS Sections 2, 8 and 11.

**Flammability**

LPS HARDCOAT CORROSION INHIBITOR is combustible, having a flash point above 100°F and an autoignition temperature over 400° F. Under normal use conditions flammability isn't a concern, but don't spray the product onto red-hot metal surfaces.

**Disposal**

If you spill LPS HARDCOAT CORROSION INHIBITOR, notify the proper environmental or safety department at your company right away. If LPS HARDCOAT CORROSION INHIBITOR becomes contaminated with another substance and is rendered unusable for protecting metal items from rust, the resulting mixture may fall under a hazardous classification. See section 13 for more details.



**LPS LABORATORIES**  
**U.S. MATERIAL SAFETY DATA SHEET**  
**LPS HardCoat Corrosion Inhibitor Bulk**

---

**Section 2 • Hazards Identification**

---

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Emergency Overview:**

**WARNING:** Flammable liquid and vapor. Keep away from heat, sparks and open flame. Contains petroleum distillates. Overexposure to vapor may cause irritation to the nose and throat and may also cause dizziness, drowsiness and other effects to the central nervous system. Use with proper ventilation. Avoid breathing vapors. Avoid eye contact. In case of eye contact, flush eyes with water and call a physician. Wash hands after use. Harmful or fatal if swallowed. Do not induce vomiting if swallowed. Call a physician immediately. Use only as directed.

**Primary route(s) of entry:** Skin and Eye contact. Inhalation.

**Potential Acute Health Effects:**

**Eyes** Irritating to eyes

**Skin** Repeated exposure may cause skin dryness or cracking. The solvent portion of this product can also be absorbed through the skin and produce CNS depression effects.

**Inhalation:** Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or headache. In extreme cases (overexposure in a confined space for example), the vapors of the solvent portion can cause disorientation, difficulty with breathing, unconsciousness, and other effects depending upon the level of overexposure and duration.

**Ingestion:** This product has a low order of acute oral toxicity, but ingestion of large quantities will cause central nervous system depression and gastrointestinal irritation. Symptoms include a burning sensation to the mouth and esophagus, nausea, vomiting, dizziness, staggering gait, drowsiness, loss of consciousness, and other central nervous system effects. May cause injury if aspirated into lungs.

**Potential Chronic Health Effects:**

**Carcinogenic Effects:** NTP: No IARC: No OSHA: No

**Mutagenic Effects:** None

**Teratogenic Effects:** None

**Medical conditions aggravated by exposure:** Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

**Signs and Symptoms**

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects.

---



**LPS LABORATORIES**  
**U.S. MATERIAL SAFETY DATA SHEET**  
**LPS HardCoat Corrosion Inhibitor Bulk**

---

**Section 3 • Composition / Information on Ingredients**

---

<b>Component</b>	<b>CASRN</b>	<b>Percent by Weight</b>
Solvent Naphtha (petroleum), medium aliphatic	64742-88-7	30 – 50%
Distillates (petroleum) hydrotreated heavy paraffinic	64742-54-7	5 – 10%
Dipropylene Glycol Methyl Ether	34590-94-8	1 - 5%
Non-hazardous ingredients*	Not applicable	40 – 60%

*\*The remaining ingredients of this preparation are not classified as hazardous per 29 CFR 1920.1200 Subpart Z*

---

**Section 4 • First Aid Measures**

---

- Eyes:** Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low-pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. Do not use eye ointment. Seek medical attention immediately.
- Skin:** Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. Do not use ointments. Seek medical attention if irritation persists.
- Inhalation:** Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek medical attention immediately.
- Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended. Seek medical attention immediately.

---

**Section 5 • Fire Fighting Measures**

---

**Flash point: (Aerosol Concentrate) CLOSED CUP:** 42° to 45°C (107° to 113°F). (Tagliabue.)

**Flammable limits:** LOWER: 0.6% UPPER: 6%    **Autoignition Temperature:** >230°C (446°F)

**Products of Combustion:** Carbon monoxide and carbon dioxide.

**Firefighting media:** SMALL FIRE: Use DRY chemical powder.  
LARGE FIRE: Use water spray, fog or foam. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosions.

**Sensitivity to Impact:** None. **Sensitivity to Static Discharge:** Yes (highly flammable propellant).

**Protection Clothing (Fire):** Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles.

**Special Remarks on Explosion Hazards:** Apply water to containers to keep them cool. Heated containers will burst.



**LPS LABORATORIES**  
**U.S. MATERIAL SAFETY DATA SHEET**  
**LPS HardCoat Corrosion Inhibitor Bulk**

---

**Section 6 • Accidental Release Measures**

---

**Small Spill and Leak:** Absorb with an inert material and dispose of properly.

**Large Spill and Leak:** For large spills, secure the area and control access. Dike far ahead of a liquid spill to ensure complete collection. Water mist or spray may be used to reduce or disperse vapors; but, it may not prevent ignition in closed spaces. This material will float on water and its run-off may create an explosion or fire hazard. Collect any excess material with absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal.

---

**Section 7 • Handling and Storage**

---

**Handling:** Eliminate ignition sources. All equipment used when handling this material must be grounded when fluid temperature exceeds 100°F. Avoid contact with eyes, skin and clothing. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists.

**Storage:** Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F.

**Precautions to be taken in handling and storage:** Store all materials in dry, well-ventilated area. Avoid breathing vapors.

---

**Section 8 • Exposure Controls / Personal Protection**

---

Ingredients	CASRN	OSHA PEL-TWA	ACGIH TLV-TWA	Other Limits
Solvent Naphtha (petroleum), medium aliphatic	64742-88-7	100 ppm	100 ppm	Not Established
Distillates (petroleum) hydrotreated heavy paraffinic	64742-54-7	5 mg/m <sup>3</sup> (Oil Mist)	5 mg/m <sup>3</sup> (Oil Mist)	10 mg/m <sup>3</sup> (Oil Mist)
Dipropylene Glycol Methyl Ether	34590-94-8	100 ppm	100 ppm	150 ppm ACGIH STEL

**Engineering Controls:** Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

**Personal Protection:**

**Eyes:** Safety glasses.

**Respiratory :** Use appropriate respirator if ventilation is inadequate.

**Hands:** Use solvent resistant gloves.

**General Hygiene Considerations:** Wash thoroughly after handling. Have eye-wash facilities immediately available.

---



**LPS LABORATORIES**  
**U.S. MATERIAL SAFETY DATA SHEET**  
**LPS HardCoat Corrosion Inhibitor Bulk**

---

**Section 9 • Physical and Chemical Properties**

---

**Physical State and Appearance:** Viscous liquid

**Vapor pressure:** 2.6 mmHg(at 20°C)

**Color:** Medium to dark brown

**Vapor density:** 4.8 (Air=1)

**Odor:** Cherry

**Volatility:** 48% (v/v)

**Boiling/Condensation point:** 160°C (320°F)

**Evaporation rate:** 0.2 (N-butylacetate = 1)

**Specific gravity:** 0.87 – 0.89 (Water=1)

**VOC:** 3.88 #/gal., 44%, 425 g/L

**Odor Threshold:** Not available.

**Solubility in water:** Insoluble in cold water.

---

**Section 10 • Stability and Reactivity**

---

**Stability and Reactivity:** The product is stable.

**Incompatibility with Various Substances:** Extremely reactive or incompatible with oxidizing agents.

**Hazardous decomposition products:** These products are carbon oxides (CO, CO<sub>2</sub>)

**Hazardous polymerization:** Will not occur.

---

**Section 11 • Toxicological Information**

---

**Acute and Chronic Toxicity**

**A: General Product Information**

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

**B: Component Analysis**

Ingredients	CASRN	LC-50	LD-50
Solvent Naphtha (petroleum), medium aliphatic	64742-88-7	Not available	Not available*
Distillates (petroleum) hydrotreated heavy paraffinic	64742-54-7	Not available	>15 gm/kg/ rat / oral >5 gm/kg/rabbit/dermal
Dipropylene Glycol Methyl Ether	34590-94-8	Not available	5400 uL/kg/rat/oral 10 mL/kg/rabbit/dermal

*\*20,000 ppm of ingredient 64742-88-7 in air can cause death to humans in 5 to 10 minutes.*

---



**LPS LABORATORIES**  
**U.S. MATERIAL SAFETY DATA SHEET**  
**LPS HardCoat Corrosion Inhibitor Bulk**

**Section 12 • Ecological Information**

**Mobility:** Semi-volatile. Readily absorbed into soil.      **Persistence and degradability:** Not readily biodegradable.

**Bioaccumulative potential:** No bioaccumulation potential      **Other adverse effects:** None known.

**Component Information**

Acute Aquatic Toxicity

Component	CASRN	Test	Species	Results
Solvent Naphtha (petroleum), medium aliphatic	64742-88-7		No Data Available	
Distillates (petroleum) hydrotreated heavy paraffinic	64742-54-7	96-hour LC <sub>50</sub>	Oncorhynchus mykiss	>1000 mg/L
Dipropylene Glycol Methyl Ether	34590-94-8		No Data Available	

If spilled, the 64742-54-7 constituent may kill grasses and small plants by interfering with transpiration. Spilled material may coat gill structures of fish resulting in suffocation if spilled in shallow, running water. This product may be toxic to amphibians by preventing dermal respiration. This product may also cause gastrointestinal distress to birds and mammals through ingestion.

**Section 13 • Disposal Considerations**

**Waste Status:** This product has the RCRA characteristic of ignitability and if discarded would have the hazardous waste code D001. In addition, "non-empty" aerosols are a RCRA hazardous waste carrying waste code D003.

**Disposal:** Waste must be disposed of in accordance with federal, state and local environmental control regulations.

**Note:** Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive than federal laws and regulations.

**Section 14 • Transport Information**

Mode	Shipping Name	Hazard Class	Number	Technical Name	Label	Packing Group	Emergency Response Guide
D.O.T. Ground	Not Regulated	NA	NA	NA	NA	NA	NA
IATA (US)	Flammable liquid, n.o.s.	3	UN 1993	Naphtha Petroleum	Flammable Liquid	III	NA
IATA (non-US)	Flammable liquid, n.o.s.	3	UN 1993	NA	Flammable Liquid	III	NA
IMDG (Regular)	Flammable liquid, n.o.s.	3	UN 1993	Naphtha Petroleum	Flammable Liquid	III	F-E, S-E



**LPS LABORATORIES**  
**U.S. MATERIAL SAFETY DATA SHEET**  
**LPS HardCoat Corrosion Inhibitor Bulk**


**Section 15 • Regulatory information**

**U.S. Federal Regulations:** **TSCA 8(b) inventory:** All of the ingredients are listed on the TSCA inventory or are exempt.  
**RCRA Hazardous Waste No.:** D001  
**CERCLA Sections 102a/103 Hazardous Substances (40 CFR part 370) Reportable Quantity:** none  
**SARA TITLE III Sections 311/312 hazardous Categorization (40 CFR part 370):** fire (flammable), acute toxicity.  
**SARA TITLE III Section 313:** No individual section 313 component is present at or above 1%.

**State Regulations:** **New Jersey RTK:** Aromatic Hydrocarbon Resin (CASRN: 68410-16-2), Solvent Naphtha (petroleum), medium aliphatic (CASRN: 64742-88-7), Distillates (petroleum) hydrotreated heavy paraffinic (CASRN: 64742-54-7), Microcrystalline Wax (63231-60-7), Dipropylene Glycol Methyl Ether (34590-94-8)

**California Proposition 65:** None.  
**California and OTC States:** This product is not regulated as a consumer item.

**Section 16 • Other Information**

<p>MSDS# 13328          Responsible Name: Ed Williams                                    <b>Technical Manager</b></p>	<p style="text-align: center;"><b>HMIS-III</b></p> <p>Health:            [*] 1          Flammability:    2          Physical Hazard: 0</p>	<p style="text-align: center;"><b>NFPA</b></p> <p style="text-align: center;">flammability</p> <div style="text-align: center;">  </div> <p style="text-align: center;">health      reactivity</p>
---	--	--

**Notice to Reader:**  
 To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Ed Williams, Technical Manager

Form #2571

LPS Laboratories  
 A division of Illinois Tool Works