



Revision Date: 03/09/2006

Issue date: 03/14/2006

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: LiteTak(R) 3751 Adhesive
Product type: Ultraviolet adhesive
Company address:
Henkel Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067

Item No. : 21363
Region: United States
Contact Information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Acrylate oligomer UNKNOWN	30-60	None	None	None
Modified acrylamide 2680-03-7	10-30	None	None	0.1 mg/m ³ TWA (skin) 0.025 ppm TWA (skin)
Substituted hydroxyalkyl methacrylate Proprietary	10-30	None	None	None
Triacrylate ester 28961-43-5	5-10	None	None	None
2-(2-Ethoxyethoxy)ethyl acrylate 7328-17-8	5-10	None	None	None
Photoinitiator 24650-42-8	1-5	None	None	None
Benzoic acid derivative 10287-53-3	1-5	None	None	None
Silica, amorphous, fumed, crystalline-free 112945-52-5	1-5	6 mg/m ³ TWA	10 mg/m ³ TWA	3 mg/m ³ TWA respirable dust
Methanol 67-56-1	0.1-1	200 ppm TWA 250 ppm STEL (skin)	200 ppm TWA 260 mg/m ³ TWA	None
Ethylene glycol 107-21-1	0.1-1	100 mg/m ³ Ceiling aerosol only	None	None

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW****HMIS:**

Physical state: Liquid
Color: Transparent to Slightly Hazy Yellow to Light amber
Odor: Mild, Ester-like, and, Amine-like

HEALTH: 2*
FLAMMABILITY: 2
PHYSICAL HAZARD: 1
Personal Protection: See Section 8

WARNING:

Item No. : 21363

Product name: LiteTak(R) 3751 Adhesive

COMBUSTIBLE LIQUID
HARMFUL IF SWALLOWED, ABSORBED THROUGH SKIN OR INHALED.
DO NOT SPRAY. DO NOT HEAT.
MAY CAUSE ALLERGIC SKIN REACTION.
CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION
SNUR ISSUED: DO NOT RELEASE TO SURFACE WATER.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation: Modified acrylamide is harmful if inhaled. Vapors and mists will irritate the respiratory tract and nasal passages. Headache. Nausea. DO NOT heat or spray as this increases the inhalation hazard. Spraying and/or heating product increases the inhalation hazard.

Skin contact: Modified acrylamide may be absorbed through skin in harmful amounts. Toxic. May cause allergic skin reaction. Irritating to skin.

Eye contact: Contact with eyes will cause irritation.

Ingestion: Modified acrylamide is harmful if swallowed. Toxic.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms develop and persist, get immediate medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and shoes. Wash clothing before reuse. Get immediate medical attention if symptoms occur.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

Flash point: 87°C (189°F) Tagliabue closed cup

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: Not available

Flammable/Explosive limits-upper %: Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special fire fighting procedures: None

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Irritating organic vapors. Toxic fumes.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Remove sources of ignition. Prevent product from entering drains or open waters.

Clean-up methods: Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent. Store in a partly filled, closed container until disposal.

Item No. : 21363

Product name: LiteTak(R) 3751 Adhesive

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. DO NOT heat or spray. Use only with adequate ventilation. Refer to Section 8. Use only in area provided with appropriate exhaust ventilation.

Storage: For safe storage, store at or below 26°C (80°F). Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

Incompatible products: Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s). If this material is handled at elevated temperatures or under mist forming conditions, without engineering controls, a NIOSH approved respirator must be used.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene gloves.

Eye/face protection: Safety goggles or safety glasses with side shields. In a splash hazard environment, chemical goggles should be used in combination with a full face shield.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Transparent to Slightly Hazy Yellow to Light amber
Odor:	Mild, Ester-like, and, Amine-like
Vapor pressure:	Less than 5 mm Hg at 20°C (68°F)
pH:	Not applicable
Boiling point/range:	Greater than 93°C (200°F)
Melting point/range:	Not available
Specific gravity:	1.062
Vapor density:	Not available
Evaporation rate:	Not available
Solubility in water:	Slight
Partition coefficient (n-octanol/water):	Not available
VOC content:	ASTM D5403 Process volatiles 0.59 %, 5.6318 grams/liter; Potential volatiles 0.50 %, 4.7727 grams/liter; Total volatiles 1.09 %, 10.4045 grams/liter.

10. STABILITY AND REACTIVITY

Stability: Unstable.

Hazardous polymerization: May occur.

Hazardous decomposition products: Oxides of carbon. Oxides of nitrogen. Oxides of phosphorous. Irritating organic vapors. Dimethylamine.

Incompatibility: Strong oxidizers. Strong acids. Strong bases.

Conditions to avoid: Heat, flames, sparks and other sources of ignition. Do not heat above 26°C (80°F).

11. TOXICOLOGICAL INFORMATION

Product toxicity data:

Modified acrylamide: LD50 (oral, rat) 316 mg/kg
 LD50 (dermal, rabbit) 518 mg/kg
 LC50 (vapor, 1hour, rat) greater than 776 ppm

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Acrylate oligomer UNKNOWN	No	No	No
Modified acrylamide 2680-03-7	No	No	No
Substituted hydroxyalkyl methacrylate Proprietary	No	No	No
Triacrylate ester 28961-43-5	No	No	No
2-(2-Ethoxyethoxy)ethyl acrylate 7328-17-8	No	No	No
Photoinitiator 24650-42-8	No	No	No
Benzoic acid derivative 10287-53-3	No	No	No
Silica, amorphous, fumed, crystalline-free 112945-52-5	No	No	No
Methanol 67-56-1	No	No	No
Ethylene glycol 107-21-1	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Acrylate oligomer UNKNOWN	No data
Modified acrylamide 2680-03-7	Less weight gain and food intake., Mutagen, Kidney, Irritant, Eyes
Substituted hydroxyalkyl methacrylate Proprietary	Allergen, Irritant
Triacrylate ester 28961-43-5	Allergen, Irritant
2-(2-Ethoxyethoxy)ethyl acrylate 7328-17-8	Allergen, Irritant
Photoinitiator 24650-42-8	No Target Organs
Benzoic acid derivative 10287-53-3	No Target Organs
Silica, amorphous, fumed, crystalline-free 112945-52-5	Nuisance dust
Methanol 67-56-1	Eyes, Heart, Irritant, Kidney, Liver, Metabolic, Nervous System, Reproductive
Ethylene glycol 107-21-1	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic

12. ECOLOGICAL INFORMATION**Ecological information:**

Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this section are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name:	Unrestricted
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA):

Proper shipping name:	Unrestricted
Hazard class or division:	None
Identification number:	None
Packing group:	None

WaterTransportation (IMO/IMDG):

Proper shipping name:	Unrestricted
Hazard class or division:	None
Identification number:	None
Packing group:	None
Marine pollutant:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	4-Methoxyphenol (150-76-5).

CERCLA/SARA Section 302 EHS:	None above reporting de minimus.
CERCLA/SARA Section 311/312:	Immediate Health Hazard, Delayed Health Hazard, Fire
CERCLA/SARA 313:	None above reporting de minimus.

California Proposition 65:	This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.
-----------------------------------	---

Canada Regulatory Information

CEPA DSL/NDL Status:	Contains one or more components listed on the Non-Domestic Substances list. All other components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class:	B.3, D.1.B, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 3,7,8

Prepared by:

Kyra Kozak Woods, Product Safety and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.