



Revision Date: 10/24/2006

Issue date: 09/07/2007

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: No More Leaks
Product type: Sealant
Company address:
Henkel Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067

Item No. : 80725
Region: United States
Contact Information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Talc 14807-96-6	30-60	2 mg/m ³ TWA particulate matter containing no asbestos and <1% crystalline silica	= 20 mppcf TWA	50 ppm
Modified maleic resin 65997-11-7	10-30	None	None	None
Methyl acetate 79-20-9	10-30	200 ppm TWA 250 ppm STEL	200 ppm TWA 610 mg/m ³ TWA	None
Polyglycol oleate 9004-96-0	10-30	None	None	None
Titanium dioxide 13463-67-7	1-5	10 mg/m ³ TWA	15 mg/m ³ TWA total dust	None
Silica, quartz 14808-60-7	0.1-1	0.025 mg/m ³ TWA respirable fraction	0.1mg/m ³ TWA (respirable)	None

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW****HMIS:**

Physical state: Liquid/paste
Color: White
Odor: Ester-like

HEALTH: 2*
FLAMMABILITY: 3
PHYSICAL HAZARD: 0
Personal Protection: See Section 8

WARNING: FLAMMABLE LIQUID AND VAPOR.
CAUSES EYE IRRITATION.
MAY CAUSE SKIN IRRITATION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Ingestion, Inhalation, Eye contact, Skin contact

Potential Health Effects

Inhalation: Vapors and mists will irritate the respiratory tract and nasal passages.
Skin contact: May cause skin irritation.
Eye contact: Contact with eyes will cause irritation.
Ingestion: May cause irritation to the gastrointestinal tract, mouth and mucous membranes.

Item No. : 80725

Product name: No More Leaks

Existing conditions aggravated by exposure:

Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation:	Remove to fresh air. If discomfort persists seek medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and shoes. Get medical attention if symptoms develop and persist.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

Flash point:	16°C (60.8°F) Pinsky Martens closed cup
Autoignition temperature:	398.3°C (750°F) estimated
Flammable/Explosive limits-lower %:	2.3 %
Flammable/Explosive limits-upper %:	12.7 %
Extinguishing media:	Use dry chemical, CO2, water spray or `alcohol` foam.
Special fire fighting procedures:	None
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions:	Do not allow material to contaminate ground water system.
Clean-up methods:	Remove all ignition sources. Maintain good ventilation for large spills. Soak up with inert absorbent. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling:	Use only with adequate ventilation. Do not get on skin or clothing. Do not get in eyes. Keep away from heat, spark and flame.
Storage:	Store away from heat, sparks, flames, or other sources of ignition. Store in original container until ready to use.
Incompatible products:	Oxidizing agents.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.
------------------------------	---

Item No. : 80725

Product name: No More Leaks

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

Eye/face protection: Chemical splash goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid/paste
Color: White
Odor: Ester-like
Vapor pressure: 33 mmHg at 20 °C (68 °F)
pH: Not applicable
Boiling point/range: 82.2°C (180°F) estimated
Melting point/range: Not available
Specific gravity: 1.42
Vapor density: 2.07
Evaporation rate: 7.7 (Ether = 1)
Solubility in water: Partial
Partition coefficient (n-octanol/water): Not determined
VOC content: 0.00%; 0.00 grams/liter (EPA Method 24)

10. STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: Will not occur.

Hazardous decomposition products: None reasonably foreseeable

Incompatibility: Oxidizing agents.

Conditions to avoid: Heat, flames and sparks.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Talc 14807-96-6	No	No	No
Modified maleic resin 65997-11-7	No	No	No
Methyl acetate 79-20-9	No	No	No
Polyglycol oleate 9004-96-0	No	No	No
Titanium dioxide 13463-67-7	No	Group 2B	Yes
Silica, quartz 14808-60-7	Known Carcinogen	Group 1	Yes

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Talc 14807-96-6	Some evidence of carcinogenicity, Lung, Irritant
Modified maleic resin 65997-11-7	No data
Methyl acetate 79-20-9	Irritant, Central nervous system, Eyes, Blood
Polyglycol oleate 9004-96-0	Irritant
Titanium dioxide 13463-67-7	Irritant, Respiratory
Silica, quartz 14808-60-7	Some evidence of carcinogenicity, Lung, Immune system

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with Federal, State and local regulations.

EPA hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The shipping classifications in this section are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: RESIN SOLUTION
 Hazard class or division: 3
 Identification number: UN 1866
 Packing group: II
 Exceptions: Consumer Commodity ORM-D (Not more than 5L)

International Air Transportation (ICAO/IATA):

Proper shipping name: RESIN SOLUTION
 Hazard class or division: 3
 Identification number: UN 1866
 Packing group: II
 Exceptions: Consumer Commodity, ID 8000, Class 9 (Not more than 500 ml)

WaterTransportation (IMO/IMDG):

Proper shipping name: RESIN SOLUTION
 Hazard class or division: 3
 Identification number: UN 1866
 Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	Methyl acetate (CAS # 79-20-9).
CERCLA/SARA Section 302 EHS:	None.
CERCLA/SARA Section 311/312:	Immediate Health Hazard, Delayed Health Hazard, Fire
CERCLA/SARA 313:	None above reporting de minimus.
California Proposition 65:	This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class:	B.2, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: First issue.

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.