



**LPS LABORATORIES
MSDS
MATERIAL SAFETY DATA SHEET**

Section 1 - Product Identification and Use

Manufacturer's Name:

LPS Laboratories

Trade Name:

ThermaPlex™ Aqua Bearing Grease

Street Address:

4647 Hugh Howell Road

Chemical Family:

Petroleum Hydrocarbons

City, State, Zip:

Tucker, GA 30085-5052

Part Numbers:

70514, 70506, 70535, 70555

Telephone Number: 770-934-7800

Emergency Telephone Number: 1-800-424-9300 Chemtrec

Outside U.S.: (703) 527-3887

Hazardous Materials Description and proper shipping name (49 CFR 172.101):

Compound, Boiler, Preserving Liquid

NMFC 50093 SUB 2 BRL/BXS CL55

TSCA Inventory:

All of the ingredients are listed on the TSCA inventory.

HMIS Labeling:

Health: 1

Flammability: 1

Reactivity: 0

Section 2 - Hazardous Ingredients / Identity Information

Ingredients	CAS Numbers	%WW	OSHA PEL	ACGIH TLV	OTHER LIMITS
Solvent refined mineral oil *Oil mist	64741-88-4	80-90	N.E.	5 mg/m3*	N.E.

Section 3 - Physical / Chemical Characteristics

Boiling point (F°): N.E. **Specific gravity (H2O = 1):** .96
Vapor pressure (mmHg) @100°F : N.E. **Percent volatile by volume (%):** 0
Vapor density (Air = 1): > 1 **Evaporation rate (n-Butyl Acetate = 1):** <1
Solubility in water: Nil

Appearance and odor: Amber, creamy paste, petroleum odor.

Section 4 - Fire and Explosion Hazard

Flash point (method used): ~ 470° F COC

Flammable limits (of diluent): LEL = N.E. UEL = N.E.

Extinguishing media: Foam, dry chemical, or carbon dioxide.

Special fire fighting procedures: Do not use water. Self-contained breathing apparatus should be provided to fire fighters. Unusual fire and explosive hazards: None

Section 5 - Health Hazard Data

N.E. = Not established
N.A. = Not applicable

Primary route(s) of entry: Eyes, skin.

Health hazard/effects of over exposure:

Inhalation: Oil mist may cause irritation of the respiratory tract.

Eyes: Irritation

Skin: Repeated or prolonged contact may cause drying and defatting of skin.

Ingestion: Not a likely route of exposure. Low order of oral toxicity; however minute amount aspirated into lungs during ingestion may cause severe pulmonary injury.

Medical conditions aggravated by exposure: None from normal exposure.

Chemicals listed as potential carcinogen: NTP: No IARC: No OSHA: No

Emergency and first aid procedures:

Inhalation: Move to fresh air and contact physician. Administer oxygen if breathing is difficult.

Eyes: Flush eyes with plenty of water and contact physician.

Skin: Wash with soap and water; apply medicated skin cream.

Ingestion: Contains petroleum oil. Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Contact physician immediately.

Section 6 - Reactivity Data

Stability: Stable **Conditions to avoid:** Extreme Heat

Incompatibility (Materials to avoid): Strong oxidizing agents.

Hazardous decomposition products: Thermal decomposition may yield, carbon monoxide, carbon dioxide, smoke, and fumes.

Hazardous polymerization: Will not occur.

Section 7 - Precautions for Safe Handling and Use

Steps to be taken in case material is released or spilled: Scoop up excess, wipe up with rags. Pick-up residue with diatomaceous earth to avoid walking hazard.

Waste disposal methods: Dispose of in accordance with local, state and federal regulations for petroleum distillates.

RCRA Hazardous Waste No.: N.A.

CERCLA Reportable Quantity: N.A.

SARA TITLE III Chemicals: Antimony compounds.

Precautions to be taken in handling and storage: Store below 150°F and above 32°F. Store away from ignition sources and avoid breathing vapors.

Section 8 - Control Measures

Respiratory Protection: None required if good ventilation is maintained.

Ventilation: Local exhaust is usually adequate.

Protective gloves: Use solvent resistant gloves for prolonged or repeated contact.

Eye protection: Use face shield or goggles if eye contact is likely.

Other protective equipment: As necessary to prevent prolonged or repeated skin contact.

Work/hygienic practices: Wash hands with soap and water after use and/or before breaks, lunch and at the end of work periods. Remove contaminated clothing and launder before reuse.

Section 9 - Preparation Date of MSDS

The foregoing technical information and recommendations are compiled from sources that are believed to be accurate and reliable. However, they are supplied without warranty or guarantee of any kind either expressed or implied. The purchaser is responsible for selecting and determining the suitability of products for purchaser's particular needs and we disclaim any responsibility for improper applications or misuse of our products in any manner whatsoever.

January 31, 2003

Fred Fugitt, Technical Services Chemist

Ed Williams, Manager of Research and Development

LPS Laboratories



Form # 2655

MSDS LPS ThermaPlex™ Aqua Bearing Grease

