

Revision Date: 12/19/2006

Issue date: 12/19/2006

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Big Foot™ Heavy Duty Pedestrian Grade  
**Product type:** Epoxy Resin  
**Company address:**  
Henkel Corporation  
1001 Trout Brook Crossing  
Rocky Hill, Connecticut 06067

**Item No. :** 96261  
**Region:** United States  
**Contact Information:**  
Telephone: 860.571.5100  
Emergency telephone: 860.571.5100  
Internet: www.loctite.com

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Nepheline syenite 37244-96-5	30-60	None	None	None
Silica, quartz 14808-60-7	10-30	0.025 mg/m <sup>3</sup> TWA respirable fraction	0.1 mg/m <sup>3</sup> TWA (respirable)	None
Xylene 1330-20-7	10-30	100 ppm TWA 150 ppm STEL	100 ppm TWA 435 mg/m <sup>3</sup> TWA	None
Aluminum oxide 1344-28-1	10-30	10 mg/m <sup>3</sup> TWA particulate matter containing no asbestos and <1% crystalline silica	15 mg/m <sup>3</sup> TWA total dust 5 mg/m <sup>3</sup> TWA respirable fraction	None
Propylene glycol monomethyl ether 107-98-2	1-5	100 ppm TWA 150 ppm STEL	None	None
Titanium dioxide 13463-67-7	0.1-1	10 mg/m <sup>3</sup> TWA	15 mg/m <sup>3</sup> TWA total dust	None

## 3. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

#### HMIS:

**Physical state:** Paste  
**Color:** Grey  
**Odor:** Mild petroleum

**HEALTH:** 2  
**FLAMMABILITY:** 3  
**PHYSICAL HAZARD:** 0  
**Personal Protection:** See Section 8

**WARNING:** FLAMMABLE LIQUID AND VAPOR.  
MAY CAUSE ALLERGIC SKIN REACTION.

**Relevant routes of exposure:** Skin contact, Eye contact, Inhalation, Ingestion

#### Potential Health Effects

**Inhalation:** Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.  
**Skin contact:** Moderate skin irritation. May cause allergic skin reaction.  
**Eye contact:** Moderate eye irritation.  
**Ingestion:** Contains material that may be slightly toxic. May be harmful if swallowed.

**Existing conditions aggravated by exposure:** Eczema. Skin allergies. Other pre-existing skin conditions.

**Item No. :** 96261

**Product name:** Big Foot™ Heavy Duty Pedestrian Grade

See Section 11 for additional toxicological information.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention.
<b>Skin contact:</b>	Remove contaminated clothing and shoes. Immediately flush skin with plenty of water (using soap, if available). Wash clothing before reuse. If skin irritation persists, call a physician.
<b>Eye contact:</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Never give anything by mouth to an unconscious person. Obtain medical attention.

#### 5. FIRE-FIGHTING MEASURES

<b>Flash point:</b>	Greater than 27.2°C (81°F) Pinsky Martens closed cup
<b>Autoignition temperature:</b>	Not available
<b>Flammable/Explosive limits-lower %:</b>	1.1 %
<b>Flammable/Explosive limits-upper %:</b>	7.0 %
<b>Extinguishing media:</b>	Carbon dioxide. Dry chemical. Foam.
<b>Special fire fighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
<b>Unusual fire or explosion hazards:</b>	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Decomposition and combustion products may be toxic.
<b>Hazardous combustion products:</b>	Oxides of carbon.

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Environmental precautions:</b>	Prevent product from entering drains or open waters.
<b>Clean-up methods:</b>	Scrape up as much material as possible. Store in a closed container until ready for disposal. Do not let product enter drains.

#### 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. Do not taste or swallow.
<b>Storage:</b>	For safe storage, store at or below 43°C (110°F). Ground and bond metal containers for liquid transfer to avoid static sparks.
<b>Incompatible products:</b>	Oxidizing agents.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Engineering controls:</b>	Use explosion-proof mechanical ventilation and local exhaust to control contaminants to within their occupational exposure limits during the use of this product. Mechanical exhaust is not recommended as the sole means of controlling employee exposure.
------------------------------	---

**Respiratory protection:** In case of insufficient ventilation wear suitable respiratory equipment. Use a NIOSH approved air purifying respirator with an organic vapor cartridge if the potential to exceed established exposure limits exists.

**Skin protection:** Chemical resistant, impermeable gloves. Neoprene gloves. Nitrile gloves. Butyl rubber gloves.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Paste  
**Color:** Grey  
**Odor:** Mild petroleum  
**Vapor pressure:** 8 mmHg @20°C (68° F)  
**pH:** Not applicable  
**Boiling point/range:** Greater than 116°C (240°F)  
**Melting point/range:** Not determined  
**Specific gravity:** 1.65  
**Vapor density:** 3.7  
**Evaporation rate:** 0.7  
**Solubility in water:** Slightly soluble  
**Partition coefficient (n-octanol/water):** Not available  
**VOC content:** Not available

## 10. STABILITY AND REACTIVITY

**Stability:** Stable.

**Hazardous polymerization:** Will not occur.

**Hazardous decomposition products:** None

**Incompatibility:** Oxidizing agents (strong)

**Conditions to avoid:** Long term exposure to elevated temperatures.

## 11. TOXICOLOGICAL INFORMATION

### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Nepheline syenite 37244-96-5	No	No	No
Silica, quartz 14808-60-7	Known Carcinogen	Group 1	Yes
Xylene 1330-20-7	No	No	No
Aluminum oxide 1344-28-1	No	No	No
Propylene glycol monomethyl ether 107-98-2	No	No	No
Titanium dioxide 13463-67-7	No	Group 2B	Yes

### Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Nepheline syenite 37244-96-5	No Target Organs
Silica, quartz 14808-60-7	Some evidence of carcinogenicity, Lung, Immune system
Xylene 1330-20-7	Cardiac, Central nervous system, Irritant, Kidney, Liver
Aluminum oxide 1344-28-1	Corrosive, Irritant, Nuisance dust
Propylene glycol monomethyl ether 107-98-2	Central nervous system, Irritant, Developmental
Titanium dioxide 13463-67-7	Irritant, Respiratory

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not applicable

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose according to EPA and local governmental regulations.

**EPA hazardous waste number:** D001: Ignitable.

## 14. TRANSPORT INFORMATION

The shipping classifications in this section are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

**U.S. Department of Transportation Ground (49 CFR):**

**Proper shipping name:** Paint  
**Hazard class or division:** 3  
**Identification number:** UN 1263  
**Packing group:** III  
**Exceptions:** (Not more than 5 L) Consumer Commodity ORM-D  
**Marine pollutant:** None

**International Air Transportation (ICAO/IATA):**

**Proper shipping name:** Paint  
**Hazard class or division:** 3  
**Identification number:** UN1263  
**Packing group:** III  
**Exceptions:** (Not more than 500 ml) May Qualify as Consumer Commodity ID8000

**Water Transportation (IMO/IMDG):**

**Proper shipping name:** Paint  
**Hazard class or division:** 3  
**Identification number:** UN1263  
**Packing group:** III  
**Marine pollutant:** None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12 (b) Export Notification:** None.

**CERCLA/SARA Section 302 EHS:** None.  
**CERCLA/SARA Section 311/312:** Immediate Health Hazard, Delayed Health Hazard, Fire  
**CERCLA/SARA 313:** Xylene (CAS# 1330-20-7).

**California Proposition 65:** This product contains a chemical known to the State of California to cause cancer.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Domestic Substances List.  
**WHMIS hazard class:** B.2, D.2.A, D.2.B

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

**Prepared by:** Rajal Dhruva, Health and Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.