



# ARMOR GUYS

• PROTECTED •

# TAEKI5

## 01-012 SPECIFICATION SHEET

### FEATURES:

#### LINER

13g, Dark Blue  
100% Taeki5® Liner

#### COATING

Black HCT MicroFoam  
Latex Palm Coating  
**Also Available In MicroFoam  
Nitrile Palm Coating**

### BENEFITS:

ANSI Cut Level A4  
EN388 Cut Level 5  
Excellent Cut Resistance  
Excellent Heat Resistance  
Excellent Abrasion Resistance  
UV Light Resistance  
Lint Free  
Moisture Wicking

### RANGE:

Taeki5®

### APPLICATIONS:


Appliance Manufacturing  
Automotive Assembly  
HVAC/Sheet Metal  
Metal Fabrication

Armor Guys reference number : 01-012



### DIMENSIONS (Inches)

	M	L	XL	XXL
A	9.1	9.4	9.8	10.2
B	3.9	4	4.1	4.3
H	Yellow	Brown	Black	Light Blue



### SPECIFICATIONS

LINER MATERIALS	Dark Blue 100% Taeki5® Liner			
COATING MATERIALS	Black HCT MicroFoam Latex			
WRIST DESIGN	Continuous Knit			
SIZES	M- XXL			
PACKAGING	1 pair in an individual polybag, 12 pairs per dozen, 120 dozen per case			
CASE	M	L	XL	XXL
WEIGHT	26.21/lbs	29.07/lbs	31.06/lbs	32.82/lbs
ORIGIN	PRC			

### PERFORMANCE LEVEL

EN388: 4544	EN Level 5 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

### TECHNOLOGIES:



Performance	TAEKI5®	HDPE* UHMWPE**	META-ARAMID PARA- ARAMID
Abrasion resistance	++	++	-
Cut resistance	++	+	-
Heat contact resistance	+	x	+
Washing	++	+	-
UV resistance	++	++	x
Lint free	++	++	x
Any Color available	++	-	-
Comfort	++	++	+
Variety of coating available including Nitrile, PVC and Latex	++	-	+
Quality/price ratio	++	-	+
<b>Total Performance</b>	+29	+19	+12

\* HDPE = High Density Polyethylene

\*\* UHMWPE = Ultra High Molecular Weight Polyethylene

Testing method based on both CE and ANSI standard

3 ++ HIGH 1 - LOW

2 + MEDIUM 0 x NO

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)