



ARMOR GUYS

• PROTECTED •

TAEKI5

01-002 SPECIFICATION SHEET

FEATURES:

LINER

10g, Yellow
100% Taeki5® Liner

COATING

Blue Crinkle Latex
Palm Coating

BENEFITS:

ANSI Cut Level A3
EN388 Cut Level 5
Excellent Cut Resistance
Excellent Heat Resistance
Excellent Abrasion Resistance
UV Light Resistance
Lint Free
Moisture Wicking

RANGE:

Taeki5®

APPLICATIONS:

Construction
Glass Handling
Mining
Steel Manufacturing
Wood Handling



SPECIFICATIONS

LINER MATERIALS	Yellow 100% Taeki5® Liner					
COATING MATERIALS	Blue Crinkle Latex					
WRIST DESIGN	Continuous Knit					
SIZES	XS- XXL					
PACKAGING	1 pair per dozen, 12 pairs per dozen, 120 Pairs per case					
CASE	XS	S	M	L	XL	XXL
WEIGHT	27.75/lbs	29.07/lbs	32.16/lbs	33.48/lbs	35.24/lbs	35.24/lbs
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4542	EN Level 5 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

TECHNOLOGIES:



Performance		TAEKI5®	HDPE* UHMWPE**	META-ARAMID PARA- ARAMID
	Abrasion resistance	++	++	-
	Cut resistance	++	+	-
	Heat contact resistance	+	x	+
	Washing	++	+	-
	UV resistance	++	++	x
	Lint free	++	++	x
	Any Color available	++	-	-
	Comfort	++	++	+
	Variety of coating available including Nitrile, PVC and Latex	++	-	+
	Quality/price ratio	++	-	+
Total Performance		+29	+19	+12

* HDPE = High Density Polyethylene

** UHMWPE = Ultra High Molecular Weight Polyethylene

Testing method based on both CE and ANSI standard

3 | ++ HIGH 1 | - LOW
2 | + MEDIUM 0 | x NO

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)