



Exceptional
Workplaces

Product Data Sheet for JACKSON SAFETY* G40 Polyurethane Coated Gloves - Hand-Specific Pairs / Grey & Black

Product Information

Customer Facing Code	38726 - 38730
Description	JACKSON SAFETY* G40 Polyurethane Coated Gloves - Hand-Specific Pairs / Grey & Black
PDS Reference	26/01/2016
Status	On Sale



Packaging Configuration

Case Contents	5 Bags x 12 Pairs = 60 Pairs
Outer Pack Material	Paper
Commodity Code	61161080

Packaging and Palletisation

Code/Size	ITF Barcode	EAN Barcode	Case LWH (cm)	Net/Gross Weight (kg)	Pallet Type	Pallet LWH (m)	Cases per Pallet
38726-7	10036000387268	036000387261	42.7 x 25.6 x 14.7	1.392/1.86	E5	1.20 x 0.80 x 1.32	6 x 8 =48
38727-8	10036000387275	036000387278	42.7 x 25.6 x 14.7	1.392/1.86	E5	1.20 x 0.80 x 1.32	6 x 8 =48
38728-9	10036000387278	036000387285	42.7 x 25.6 x 14.7	1.392/1.86	E5	1.20 x 0.80 x 1.32	6 x 8 =48
38729-10	10036000387299	036000387292	42.7 x 25.6 x 14.7	1.392/1.86	E5	1.20 x 0.80 x 1.32	6 x 8 =48
38730-11	10036000387305	036000387380	42.7 x 25.6 x 14.7	1.392/1.86	E5	1.20 x 0.80 x 1.32	6 x 8 =48

Product Description

JACKSON SAFETY* G40 Grey PU+ Gloves are suitable for tasks and processes where there is a need to protect workers' hands against mechanical hazards. They provide users with PPE Category 2 hand protection in general purpose, warehousing, and general industrial applications where general hand protection is required.

Ideal for assembly and/or finishing applications in Automotive, Aerospace, Metal Manufacturing and Constructions, but also in other segments where there is a need to avoid breaking or tearing allowing sensitive touch for handling small parts.

Available as pairs of hand specific 15 gauges gloves with grey polyurethane coating for excellent dexterity and sensitivity in light/medium assembly tasks plus superior wet/dry grip and oil repellency; the seamless knitted nylon backing offers breathability and comfort.

Features and Benefits

Features

- Roughened grey polyurethane coated palm**
- Seamless 15 gauges nylon knitted shell**

Benefits

- To offer excellent oil repellency, mechanical protection for dry and/or slightly oily tasks and excellent grip
- To provide breathability and comfort but also dexterity and protection for light/medium assembly applications

Product Data Sheet for JACKSON SAFETY* G40 Polyurethane Coated Gloves - Hand-Specific Pairs / Grey & Black

Product Configuration

Sterile	No	Latex Free	Yes
Main Protection Type	CE Intermediate	Application	Industrial
Ambidextrous	No	Powdered	No
Material	Nylon	Coated	Palm Coated
Liner	Seamless Knitted Black Shell	Coating	Grey Polyurethane
Colour	Grey & Black	Cuff Style	Knitwrist
Gauge	15	Glove Shape	Hand Specific
Length	220 - 260 mm		

International Standards and Symbols

Solution

Safer Workplace

We know staff safety is your top priority. You can rely on our solutions to protect them, their environment and your important work.



Productive Workplace

The success of your business hinges on your work efficiency. That's why our solutions are designed to help improve your productivity.



Standard R+E

EN 388:2003

This standard which is designed to assess the performance of a fabric or layers of fabric for their ability to resist mechanical risks of abrasion, blade cut, tear and puncture. The test procedure includes a separate test for each of these properties, and a performance level is awarded according to each test result. This standard is only applicable in conjunction with EN420



CE Mark

Simple - CAT I, Intermediate - CAT II or Complex - CAT III



Trade

ISO 9001

This gives the requirements for quality management systems, is now firmly established as the globally implemented standard for providing assurance about the ability to satisfy quality requirements and to enhance customer satisfaction in supplier-customer relationships.



Packaging

Unit Of Sale	Case	Max Weight(kg)	2.05
Case Dimension(LXWXH)(cm)	42.7 x 25.6 x 14.7	Inner Pack Material	Paper

Product Data Sheet for JACKSON SAFETY* G40 Polyurethane Coated Gloves - Hand-Specific Pairs / Grey & Black

Instructions

The open book pictogram - indicates that the user should read and understand the USER INSTRUCTIONS before using the garment.



Protect from heat and radioactive sources.



Keep Dry. Store in a cool, dry place.



Information

It is the employer's responsibility to assess the risk of the task to be undertaken and determine the correct choice of personal protective equipment for the task. The manufacturer, Kimberly-Clark, does not accept any responsibility for the incorrect choice or misuse of the personal protective equipment shown in this brochure. All care has been taken to ensure that the information contained herein is as accurate as possible at the time of publication, however errors may occur and legislation concerning personal protective equipment is under constant review and may change in the lifetime of this brochure. Accordingly, the specification for the products may be subject to change. We would advise you to contact INFOFAX if you have any queries concerning the products shown or the suitability of such products for a particular task. Always dispose of used protective equipment in a safe and appropriate manner in accordance with European, National and Local environmental regulations.

Infofax Details

infofax@kcc.com

Websites

www.kcprofessional.co.uk

Storage conditions

Keep dry. Store in a cool dry place and shield from exposure to direct sunlight, intense artificial light or exposure to sources of radiation or ozone.

Durability

This product has a five years shelf life from the date of manufacture.

Customer Service Number

For more information please contact Customer Service during regular office hours-0870 551 044

Country of Origin

SRI LANKA