

LEVERAGING TECHNOLOGIES TO REDUCE INJURIES



Model Shown
3601490

- **PIVOTING ANCHOR AND CARABINER**
Centers the load and is large for an easy connection
- **ALUMINUM HOUSING**
Provides exceptional strength, durability, and corrosion resistance
- **SEALED DESIGN**
Ensures efficient, safe operation under the harshest working conditions
- **CARRYING HANDLE**
Built-in design for easy transport, and can be used for dropped objects protection
- **STAINLESS STEEL CABLE**
Resists abrasion and corrosion
- **8 FT. (2.4 M) TAIL with CLEAR TUBE**
Protects cable in the work environment and allows for easy inspection
- **ERGONOMIC CABLE HANDLE**
Provides added comfort and ease-of-use when making connections
- **STAINLESS STEEL TRIPLE LOCKING SWIVEL HOOK with 3600 LB. (16 KN) GATE**
Limits lifeline twisting

Equipped with



LIMIT FORCES. WARN OPERATOR. REDUCE INJURY.

LEVERAGING SEALED-BLOK™ TECHNOLOGY

The Sealed Tension Limiter™ connects in line between the suspended worker and the winch line. If the worker becomes entangled, the deployment of a bright yellow cable cues the crane operator to stop. When the Sealed Tension Limiter™ deploys, it limits loads to reduce the possibility of severe injury. Following the activation, the device automatically resets.



DURABLE

Heavy-duty design stands up to the harshest environments

- Corrosion resistant
- Stainless steel end-plates
- Aluminum housing

RELIABLE

Dynamic components sealed inside the housing to protect against moisture/water penetration and the finest particulate contaminants.

TRUSTED

The Sealed Tension Limiter™ design is based upon proven DBI-SALA® Sealed-Blok™ technology to ensure that the Sealed Tension Limiter™ will perform in any environment and endure virtually any condition.

SPECIFICATIONS:

Model: 3601490

Rated Capacity: 130-310 lbs. (59-141 kg) (Single user only)

Total Deployment: 23 ft. (7 m)

Weight: 21.3 lbs. (9.7 kg)

General Construction: Aluminum and stainless steel components

Lifeline Material: Stainless steel

Carabiner: Stainless steel, 3,600 lb. (16 kN) triple action

Deployment Force: 400-900 lbs. (181-408 kg)

PLEASE NOTE: THIS PRODUCT ALONE WILL NOT MAKE A MATERIAL WINCH A MAN-RATED WINCH.

The Sealed Tension Limiter™ is designed to limit the loading force a person could be subjected to should they become entangled in the structure while the main winch line continues to operate. ALWAYS use a separate fall protection device with the Sealed Tension Limiter™ device.



Capital Safety - USA: 800 328 6146
Canada: 800 387 7484 | Latin America: +1 651 385 4301
Asia: +65 65587758 | Germany: +49 (0)30 92 03 83 87 00
New Zealand: 0800 212 505 | Australia: 1800 245 002
Europe, Middle East, Africa: +33 (0)4 97 10 00 10
Northern Europe: +44 (0)1928 571234
www.capitalsafety.com info@capitalsafety.com