



## Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 23-2818-5 | <b>Version Number:</b>  | 1.25     |
| <b>Issue Date:</b>     | 01/16/15  | <b>Supersedes Date:</b> | 10/23/14 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Abrasive Products, Diamond Resin or Poly Bond Grinding Wheels

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Abrasive Product

#### 1.3. Supplier's details

|                      |                                         |
|----------------------|-----------------------------------------|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Abrasive Systems Division               |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Skin Sensitizer: Category 1.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Exclamation mark | Health Hazard |

##### Pictograms



**Hazard Statements**

May cause an allergic skin reaction.  
Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:  
respiratory system |

**Precautionary Statements****Prevention:**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wear protective gloves.  
Do not eat, drink or smoke when using this product.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
IF exposed or concerned: Get medical advice/attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

None.

**SECTION 3: Composition/information on ingredients**

| <b>Ingredient</b>                    | <b>C.A.S. No.</b> | <b>% by Wt</b> |
|--------------------------------------|-------------------|----------------|
| Diamond                              | 7782-40-3         | 5 - 20         |
| Copper                               | 7440-50-8         | 0 - 49         |
| Aluminum Oxide Mineral (non-fibrous) | 1344-28-1         | 0 - 40         |
| Silicon Carbide Mineral              | 409-21-2          | 0 - 40         |
| Tin                                  | 7440-31-5         | 0 - 10         |
| Glass                                | 65997-17-3        | 0 - 10         |
| Silver                               | 7440-22-4         | 0 - 10         |
| Calcium Oxide                        | 1305-78-8         | 0 - 6          |
| Nickel                               | 7440-02-0         | 0 - 5          |
| Lubricant                            | 7782-42-5         | 0 - 3          |
| Cured Resin                          | Mixture           | 10 - 40        |
| Cores                                | Mixture           | Not Applicable |

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

**Substance**

Carbon monoxide

Carbon dioxide

Hydrogen Gas

**Condition**

During Combustion

During Combustion

During Combustion

**5.3. Special protective actions for fire-fighters**

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Not applicable.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**

For industrial or professional use only. Avoid breathing of dust created by sanding, grinding or machining. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks

prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required. Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

## 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient                           | C.A.S. No. | Agency                  | Limit type                                                   | Additional Comments            |
|--------------------------------------|------------|-------------------------|--------------------------------------------------------------|--------------------------------|
| Calcium Oxide                        | 1305-78-8  | ACGIH                   | TWA:2 mg/m3                                                  |                                |
| Calcium Oxide                        | 1305-78-8  | OSHA                    | TWA:5 mg/m3                                                  |                                |
| Aluminum Oxide Mineral (non-fibrous) | 1344-28-1  | CMRG                    | TWA:1 fiber/cc                                               |                                |
| Aluminum Oxide Mineral (non-fibrous) | 1344-28-1  | OSHA                    | TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3 |                                |
| Aluminum, insoluble compounds        | 1344-28-1  | ACGIH                   | TWA(respirable fraction):1 mg/m3                             | A4: Not class. as human carcin |
| Silcon Carbide Mineral               | 409-21-2   | OSHA                    | TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3 |                                |
| CERAMIC FIBERS                       | 65997-17-3 | ACGIH                   | TWA(as fiber):0.2 fiber/cc                                   | A2: Suspected human carcin.    |
| Glass                                | 65997-17-3 | Manufacturer determined | TWA(as dust):10 mg/m3                                        |                                |
| Nickel                               | 7440-02-0  | ACGIH                   | TWA(inhalable fraction):1.5 mg/m3                            | A5: Not suspected human carcin |
| Nickel                               | 7440-02-0  | OSHA                    | TWA(as Ni):1 mg/m3                                           |                                |
| Silver                               | 7440-22-4  | ACGIH                   | TWA(as dust and fume):0.1 mg/m3                              |                                |
| Silver                               | 7440-22-4  | OSHA                    | TWA(as Ag):0.01 mg/m3                                        |                                |
| Tin                                  | 7440-31-5  | ACGIH                   | TWA:2 mg/m3                                                  |                                |
| Tin                                  | 7440-31-5  | OSHA                    | TWA(as Sn):2 mg/m3                                           |                                |
| Copper                               | 7440-50-8  | OSHA                    | TWA(as Cu dust or mist):1 mg/m3;TWA(as Cu, fume):0.1 mg/m3   |                                |
| GRAPHITE SYNTHETIC                   | 7782-42-5  | OSHA                    | TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3 |                                |
| Lubricant                            | 7782-42-5  | ACGIH                   | TWA(respirable fraction):2 mg/m3                             |                                |
| Lubricant                            | 7782-42-5  | OSHA                    | TWA:15 millions of particles/cu. ft.                         |                                |

ACGIH : American Conference of Governmental Industrial Hygienists  
AIHA : American Industrial Hygiene Association  
CMRG : Chemical Manufacturer's Recommended Guidelines  
OSHA : United States Department of Labor - Occupational Safety and Health Administration  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

## **8.2. Exposure controls**

### **8.2.1. Engineering controls**

Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

### **8.2.2. Personal protective equipment (PPE)**

#### **Eye/face protection**

To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:  
Safety Glasses with side shields

#### **Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### **Respiratory protection**

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:  
Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

|                               |                        |
|-------------------------------|------------------------|
| <b>General Physical Form:</b> | Solid                  |
| <b>Odor, Color, Grade:</b>    | Solid Abrasive Product |
| <b>Odor threshold</b>         | <i>Not Applicable</i>  |

|                                         |                       |
|-----------------------------------------|-----------------------|
| pH                                      | <i>Not Applicable</i> |
| Melting point                           | <i>Not Applicable</i> |
| Boiling Point                           | <i>Not Applicable</i> |
| Flash Point                             | <i>Not Applicable</i> |
| Evaporation rate                        | <i>Not Applicable</i> |
| Flammability (solid, gas)               | Not Classified        |
| Flammable Limits(LEL)                   | <i>Not Applicable</i> |
| Flammable Limits(UEL)                   | <i>Not Applicable</i> |
| Vapor Pressure                          | <i>Not Applicable</i> |
| Vapor Density                           | <i>Not Applicable</i> |
| Specific Gravity                        | <i>Not Applicable</i> |
| Solubility In Water                     | <i>Not Applicable</i> |
| Solubility- non-water                   | <i>Not Applicable</i> |
| Partition coefficient: n-octanol/ water | <i>Not Applicable</i> |
| Autoignition temperature                | <i>Not Applicable</i> |
| Decomposition temperature               | <i>Not Applicable</i> |
| Viscosity                               | <i>Not Applicable</i> |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below). Dust from grinding, sanding or machining may cause target organ effects.

**Skin Contact:**

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

May be harmful if swallowed.

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Dermal Effects: Signs/symptoms may include changes in skin pigmentation and/or coloration.

**Prolonged or repeated exposure may cause target organ effects:**

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

| <b>Ingredient</b>        | <b>CAS No.</b> | <b>Class Description</b>       | <b>Regulation</b>                           |
|--------------------------|----------------|--------------------------------|---------------------------------------------|
| Generic: GLASS FILAMENTS | 65997-17-3     | Anticipated human carcinogen   | National Toxicology Program Carcinogens     |
| NICKEL COMPOUNDS         | 7440-02-0      | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| Generic: CERAMIC FIBERS  | 65997-17-3     | Grp. 2B: Possible human carc.  | International Agency for Research on Cancer |
| Generic: CERAMIC FIBERS  | 65997-17-3     | Anticipated human carcinogen   | National Toxicology Program Carcinogens     |
| Nickel                   | 7440-02-0      | Grp. 2B: Possible human carc.  | International Agency for Research on Cancer |
| Nickel                   | 7440-02-0      | Anticipated human carcinogen   | National Toxicology Program Carcinogens     |

**Additional Information:**

This document covers only the 3M product. For complete assessment, when determining the degree of hazard, the material being abraded must also be considered.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| <b>Name</b>     | <b>Route</b>         | <b>Species</b> | <b>Value</b>                                          |
|-----------------|----------------------|----------------|-------------------------------------------------------|
| Overall product | Ingestion            |                | No data available; calculated ATE 2,000 - 5,000 mg/kg |
| Copper          | Dermal               | Rat            | LD50 > 2,000 mg/kg                                    |
| Copper          | Inhalation-Dust/Mist | Rat            | LC50 > 5.11 mg/l                                      |

|                                      |                                |     |                                          |
|--------------------------------------|--------------------------------|-----|------------------------------------------|
|                                      | (4 hours)                      |     |                                          |
| Copper                               | Ingestion                      | Rat | LD50 > 2,000 mg/kg                       |
| Aluminum Oxide Mineral (non-fibrous) | Dermal                         |     | LD50 estimated to be > 5,000 mg/kg       |
| Aluminum Oxide Mineral (non-fibrous) | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 2.3 mg/l                          |
| Aluminum Oxide Mineral (non-fibrous) | Ingestion                      | Rat | LD50 > 5,000 mg/kg                       |
| Silicon Carbide Mineral              | Dermal                         | Rat | LD50 > 2,000 mg/kg                       |
| Silicon Carbide Mineral              | Ingestion                      | Rat | LD50 > 2,000 mg/kg                       |
| Glass                                | Dermal                         |     | LD50 estimated to be > 5,000 mg/kg       |
| Glass                                | Ingestion                      |     | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Silver                               | Ingestion                      | Rat | LD50 > 2,000 mg/kg                       |
| Tin                                  | Dermal                         | Rat | LD50 > 2,000 mg/kg                       |
| Tin                                  | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 4.75 mg/l                         |
| Tin                                  | Ingestion                      | Rat | LD50 > 2,000 mg/kg                       |
| Calcium Oxide                        | Ingestion                      | Rat | LD50 500-2000 mg/kg                      |
| Nickel                               | Dermal                         |     | LD50 estimated to be > 5,000 mg/kg       |
| Nickel                               | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 2.55 mg/l                         |
| Nickel                               | Ingestion                      | Rat | LD50 > 9,000 mg/kg                       |
| Lubricant                            | Ingestion                      | Rat | LD50 > 2,000 mg/kg                       |

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

| Name                                 | Species                 | Value                     |
|--------------------------------------|-------------------------|---------------------------|
| Copper                               | Rabbit                  | No significant irritation |
| Aluminum Oxide Mineral (non-fibrous) | Rabbit                  | No significant irritation |
| Silicon Carbide Mineral              | Rat                     | No significant irritation |
| Glass                                | Professional judgement  | No significant irritation |
| Tin                                  | Rabbit                  | No significant irritation |
| Calcium Oxide                        | official classification | Corrosive                 |
| Nickel                               | Rabbit                  | Minimal irritation        |
| Lubricant                            | Rabbit                  | No significant irritation |

#### Serious Eye Damage/Irritation

| Name                                 | Species                | Value                     |
|--------------------------------------|------------------------|---------------------------|
| Copper                               | Rabbit                 | Mild irritant             |
| Aluminum Oxide Mineral (non-fibrous) | Rabbit                 | No significant irritation |
| Silicon Carbide Mineral              | Professional judgement | No significant irritation |
| Glass                                | Professional judgement | No significant irritation |
| Tin                                  | Rabbit                 | No significant irritation |
| Calcium Oxide                        | Rabbit                 | Corrosive                 |
| Nickel                               | Rabbit                 | Mild irritant             |
| Lubricant                            | Rabbit                 | No significant irritation |

#### Skin Sensitization

| Name   | Species | Value       |
|--------|---------|-------------|
| Nickel | Human   | Sensitizing |

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

| Name                                 | Route    | Value                                                                        |
|--------------------------------------|----------|------------------------------------------------------------------------------|
| Aluminum Oxide Mineral (non-fibrous) | In Vitro | Not mutagenic                                                                |
| Glass                                | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Calcium Oxide                        | In Vitro | Not mutagenic                                                                |
| Lubricant                            | In Vitro | Some positive data exist, but the data are not sufficient for classification |

**Carcinogenicity**

| Name                                 | Route      | Species                 | Value                                                                        |
|--------------------------------------|------------|-------------------------|------------------------------------------------------------------------------|
| Aluminum Oxide Mineral (non-fibrous) | Inhalation | Rat                     | Not carcinogenic                                                             |
| Glass                                | Inhalation | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| Nickel                               | Inhalation | similar compounds       | Carcinogenic                                                                 |

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

| Name          | Route      | Target Organ(s)        | Value                            | Species       | Test Result         | Exposure Duration     |
|---------------|------------|------------------------|----------------------------------|---------------|---------------------|-----------------------|
| Calcium Oxide | Inhalation | respiratory irritation | May cause respiratory irritation | Not available | NOAEL Not available | occupational exposure |

**Specific Target Organ Toxicity - repeated exposure**

| Name                                 | Route      | Target Organ(s)                     | Value                                                                        | Species | Test Result         | Exposure Duration     |
|--------------------------------------|------------|-------------------------------------|------------------------------------------------------------------------------|---------|---------------------|-----------------------|
| Aluminum Oxide Mineral (non-fibrous) | Inhalation | pneumoconiosis   pulmonary fibrosis | Some positive data exist, but the data are not sufficient for classification | Human   | NOAEL Not available | occupational exposure |
| Glass                                | Inhalation | respiratory system                  | Some positive data exist, but the data are not sufficient for classification | Human   | NOAEL not available | occupational exposure |
| Nickel                               | Inhalation | respiratory system                  | Causes damage to organs through prolonged or repeated exposure               | Rat     | LOAEL 0.001 mg/l    | 13 weeks              |
| Lubricant                            | Inhalation | pneumoconiosis                      | Some positive data exist, but the data are not sufficient for classification | Human   | NOAEL Not available | occupational exposure |

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

**EPA Hazardous Waste Number (RCRA):** D011 (Silver)

## SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

*These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and **not the packaging, labeling, or marking requirements**. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.*

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No    Pressure Hazard - No    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - Yes

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

| <u>Ingredient</u>         | <u>C.A.S. No</u> | <u>% by Wt</u> |
|---------------------------|------------------|----------------|
| Nickel                    | 7440-02-0        | 0 - 5          |
| Nickel (Nickel)           | 7440-02-0        | 0 - 5          |
| Nickel (NICKEL COMPOUNDS) | 7440-02-0        | 0 - 5          |
| Copper                    | 7440-50-8        | 0 - 49         |
| Copper (Copper)           | 7440-50-8        | 0 - 49         |
| Silver                    | 7440-22-4        | 0 - 10         |
| Silver (Silver)           | 7440-22-4        | 0 - 10         |

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health:** \*2 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 23-2818-5 | <b>Version Number:</b>  | 1.25     |
| <b>Issue Date:</b>     | 01/16/15  | <b>Supersedes Date:</b> | 10/23/14 |

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**