



SPECIFICATION SHEET

390-EZ150

EZ® COOL EVAPORATIVE COOLING TANK TOP

- Lightweight, athletic design that features a nylon/spandex outer shell and inner HyperKewl™ cooling fabric with water repellent liner
- 1-2 minute activation time
- Can provide 5-10 hours of cooling relief per activation
- Cools the body 15-20 degrees from the ambient temperature
- Provides uniform cooling affect without the swelling and slime affect
- Dries after use and when stored properly eliminates the chance of mold or mildew
- Side zip closure for easy on/off
- Built-in ventilation on sides and back
- Machine washable

APPLICATIONS

- Roadway construction workers
- Mining
- Farming
- Emergency response personnel
- Industrial sites
- Sporting events

CARE INSTRUCTIONS

Always store in clean, dry conditions. DO NOT store in places subject to direct, strong sunlight. Spot wash or hand wash ONLY.

TECHNICAL DATA

MATERIAL	Spandex / Nylon
COLOR	■ Black with Blue Trim
SIZES	XS - 3X
PACKAGING	1 per poly bag, 25 per case
CASE DIMENSIONS	16" x 16" x 10" / 40.6cm x 40.6cm x 25.4cm
CASE WEIGHT	48lbs / 21.8kg
COO	China


BARCODES

ITEM	BAG	DOZEN	CASE
■ 390-EZ150-LY/S	616314222849	01616314222848	02616314222847
■ 390-EZ150-LY/M	616314222856	01616314222855	02616314222854
■ 390-EZ150-LY/L	616314222863	01616314222862	02616314222861
■ 390-EZ150-LY/XL	616314222870	01616314222879	02616314222878
■ 390-EZ150-LY/2X	616314222887	01616314222886	02616314222885
■ 390-EZ150-LY/3X	616314222894	01616314222893	02616314222892



DIMENSIONS (in/cm)

	XS	S	M	L	XL	2X	3X
A	33 / 83.8	36 / 91.4	39 / 99.1	42 / 106.7	45 / 114.3	48 / 121.9	51 / 129.5
B	20 / 50.8	20.5 / 52.1	21 / 53.3	21.5 / 54.6	22 / 55.9	23.5 / 59.7	25 / 63.5



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.