



Revision Number: 007.0

Issue date: 08/07/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE PC 7313 known as Nordbak Chem Resis Coating	IDH number:	702186
Product type:	Epoxy Hardener	Item number:	96092_369000
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: +1 (860) 571-5100		
Henkel Way One	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1C
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

PICTOGRAM(S)**Precautionary Statements**

Prevention:	Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.
Response:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 702186

Product name: LOCTITE PC 7313 known as Nordbak Chem Resis Coating
Page 1 of 6

Hazardous Component(s)	CAS Number	Percentage*
Benzyl alcohol	100-51-6	30 - 40
Formaldehyde, polymer with benzenamine, hydrogenated	135108-88-2	30 - 40
Salicylic acid	69-72-7	5 - 10
m-Phenylenebis(methylamine)	1477-55-0	1 - 5
4,4'-Methylenebis(cyclohexylamine)	1761-71-3	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray. Burning produces obnoxious and toxic fumes. Personnel in vicinity and downwind should be evacuated. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from fire fighting to enter drains or water courses. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Ammonia. Aldehydes. Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed.
Storage:	Store in original container until ready to use. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Benzyl alcohol	None	None	10 ppm (44.20 mg/m3) TWA	None
Formaldehyde, polymer with benzenamine, hydrogenated	None	None	None	None
Salicylic acid	None	None	None	None
m-Phenylenebis(methylamine)	0.1 mg/m3 Ceiling (SKIN)	None	None	None
4,4'-Methylenebis(cyclohexylamine)	None	None	None	None

Engineering controls:	Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.
Respiratory protection:	Use a NIOSH approved supplied air respirator with an organic cartridge if the potential to exceed established exposure limits exists.
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.
Skin protection:	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Light yellow
Odor:	Ammonia
Odor threshold:	Not available.
pH:	Alkaline
Vapor pressure:	Not available.
Boiling point/range:	204 °C (399.2 °F)
Melting point/ range:	Not available.
Specific gravity:	1.0242
Vapor density:	> 1 (Air = 1)
Flash point:	> 100 °C (> 212°F) Setflash Closed Cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	< 1 (Butyl acetate = 1)
Solubility in water:	Appreciable
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 1 %; < 10 g/l (value for resin and hardener together) (estimated)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Ammonia. Aldehydes. Toxic fumes. Irritating vapors.
Incompatible materials:	Acids. Bases. Oxidizing agents. Reducing agents. Sodium hypochlorite. Peroxides. Nitrous acid and other nitrosating agents. CAUTION! N-nitrosamines (many of which are known to be potent carcinogens) may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations. This product slowly corrodes copper, aluminum, zinc and galvanized surfaces.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Mists, vapors or liquid may cause severe irritation or burns.
Skin contact:	Causes skin burns. May cause allergic skin reaction. Tissue damage. Itching. Rash. Redness.
Eye contact:	Causes serious eye damage. Burns. May cause permanent visual impairment. Tissue damage. Blurred vision. Redness. Tearing. Pain and discomfort.
Ingestion:	If ingested, severe burns of the mouth and throat may occur, as well as perforation of the esophagus and the stomach. May cause an aspiration hazard if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Benzyl alcohol	Oral LD50 (Rabbit) = 1,940 mg/kg Oral LD50 (Rat) = 1,230 - 3,100 mg/kg Oral LD50 (Mouse) = 1,580 mg/kg Oral LD50 (Rat) = 3,100 mg/kg Dermal LD50 (Rabbit) = 2,000 mg/kg	Allergen, Central nervous system, Corrosive, Irritant
Formaldehyde, polymer with benzenamine, hydrogenated	None	No Records
Salicylic acid	Oral LD50 (Rat) = 891 mg/kg Oral LD50 (Mouse) = 480 mg/kg Dermal LD50 (Rat) = > 2 g/kg	Irritant
m-Phenylenebis(methylamine)	None	Irritant, Liver, Kidney, Corrosive
4,4'-Methylenebis(cyclohexylamine)	None	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Benzyl alcohol	No	No	No
Formaldehyde, polymer with benzenamine, hydrogenated	No	No	No
Salicylic acid	No	No	No
m-Phenylenebis(methylamine)	No	No	No
4,4'-Methylenebis(cyclohexylamine)	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Follow all local, state, federal and provincial regulations for disposal.
Hazardous waste number:	It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of Ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Amines, liquid, corrosive, n.o.s. (1,3-Benzenedimethanamine)
Hazard class or division:	8
Identification number:	UN 2735
Packing group:	III

International Air Transportation (ICAO/IATA)

Proper shipping name:	Amines, liquid, corrosive, n.o.s. (1,3-Benzenedimethanamine)
Hazard class or division:	8
Identification number:	UN 2735
Packing group:	III

Water Transportation (IMO/IMDG)

Proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine)
Hazard class or division:	8
Identification number:	UN 2735
Packing group:	III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA Section 313:	None above reporting de minimis.
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,11

Prepared by:	Rebecca Coons, Regulatory Affairs Specialist
Issue date:	08/07/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.