

DRY FILM SILICONE LUBRICANT



The dry film silicone lubricant for rubber, plastic and metal parts.

- Provides excellent lubrication
- Ideal for releasing molded parts
- Excellent for high temperature applications up to 500°F
- Colorless, thin film
- Dry film will not attract dust or dirt
- Nonflammable
- Does not contain chlorinated solvents

Dry Film Silicone Lubricant is available in this size:

12 oz. (340 grams) aerosol Part No. 01616

Typical applications where Dry Film Silicone Lubricant can be used:

- Compression Molding
- Conveyors
- Doors
- Injection Molding
- Plastic Gears
- Rubber Components
- Slides
- Sliding Wood Surfaces
- Windows

General Information

Dry Film Silicone Lubricant is excellent for applications involving rubber, plastic, and metal parts. Dry Film Silicone Lubricant provides excellent lubrication and is ideal for releasing molded parts. It has a dry film which will not attract dust or dirt, and it is excellent for high temperature applications.

Material Safety Data Sheets are available upon request.

Properties

Active Ingredient:
Silicone

Propellant:
Oxygenated Hydrocarbon/HFC

Flammability:
Nonflammable

Properties of Non-Volatiles

Color/Form:
Clear, Colorless Liquid

Viscosity @ 77°F:
350cSt

Temperature Range:
-40°F to 500°F



LPS Laboratories • An Illinois Tool Works Company
P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 U.S.A.
TEL: (800) 241-8334 or (770) 934-7800 • FAX: (800) 543-1563 or (770) 493-9206
Internet Web Site: www.lpslabs.com

LPS® is a registered trademark of LPS Laboratories • ©2001 LPS Laboratories • All Rights Reserved • Rev. 09/2001 • Form #X2135-7

CERTIFIED
ISO 9001
QUALITY MANAGEMENT SYSTEM