

Safety Data Sheet

Copyright,2016,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	08-3432-5	Version Number:	24.01
Issue Date:	11/03/16	Supercedes Date:	05/08/15

SECTION 1: Identification

1.1. Product identifier

3M[™] Fastbond[™] Foam Adhesive 100

Product Identification Numbers

62-4284-6535-5, 62-4284-8436-4, 62-4284-8530-4, 62-4284-9530-3, 62-4284-9538-6, 62-4284-9932-1

1.2. Recommended use and restrictions on use

Recommended use Adhesive, Industrial use

1.3. Supplier's details	
MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Reproductive Toxicity: Category 1B.

2.2. Label elements Signal word Danger

Symbols Health Hazard |

Pictograms



Hazard Statements May damage fertility or the unborn child.

Precautionary Statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye/face protection.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	50 - 60 Trade Secret *
Polychloroprene	9010-98-4	40 - 50 Trade Secret *
Sodium Soap of Disproportationed Rosin	61790-51-0	1 - 5 Trade Secret *
Boric Acid	10043-35-3	< 1 Trade Secret *
Zinc Oxide	1314-13-2	< 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If you are concerned, get medical advice.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Carbon monoxide Carbon dioxide Oxides of Nitrogen <u>Condition</u> During Combustion During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing

3MTM FastbondTM Foam Adhesive 100 11/03/16

agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Boric Acid	10043-35-3	ACGIH	TWA(inhalable fraction):2	A4: Not class. as human
			mg/m3;STEL(inhalable	carcin
			fraction):6 mg/m3	
Zinc Oxide	1314-13-2	ACGIH	TWA(respirable fraction):2	
			mg/m3;STEL(respirable	
			fraction):10 mg/m3	
Zinc Oxide	1314-13-2	OSHA	TWA(as fume):5	
			mg/m3;TWA(as total dust):15	
			mg/m3;TWA(respirable	
			fraction):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene Nitrile Rubber Natural Rubber

Respiratory protection

3M TM Fastbond TM Fo	oam Adhesive 100	11/03/16
--	------------------	----------

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

Boiling Point>=215 °FFlash PointNo flash pointEvaporation rate1 [Ref Std: WATER=1]Flammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor Pressure17.5 mmHg [@ 68 °F]Vapor Density1.10 [Ref Std: AIR=1]Density1.1 g/mlSpecific Gravity1.1 [Ref Std: WATER=1]Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]Molecular weightNo Data Available	General Physical Form:	Liquid
pH8.4 - 9Melting pointNot ApplicableBoiling Point>=215 °FFlash PointNo flash pointEvaporation rate1 [Ref Std: WATER=1]Flammability (solid, gas)Not ApplicableFlammabile Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor Pressure17.5 mmHg [@ 68 °F]Vapor Density1.10 [Ref Std: AIR=1]Density1.1 [Ref Std: WATER=1]Solubility in WaterModerateSolubility - non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]Molecular weightNo Data AvailableVOC Less H2O & Exempt Solvents<=20 g/l [Test Method: calculated SCAQMD rule 443.1	Odor, Color, Grade:	rubber odor, thin liquid, white
Melting pointNot ApplicableBoiling Point>=215 °FFlash PointNo flash pointEvaporation rate1 [Ref Std: WATER=1]Flammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor Pressure17.5 mmHg [@ 68 °F]Vapor Density1.10 [Ref Std: WATER=1]Density1.1 g/mlSpecific Gravity1.1 [Ref Std: WATER=1]Solubility in WaterNo Data AvailableSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]Molecular weightNo Data AvailableVOC Less H2O & Exempt Solvents<=20 g/l [Test Method: calculated SCAQMD rule 443.1	Odor threshold	No Data Available
Boiling Point>=215°FFlash PointNo flash pointEvaporation rate1 [Ref Std: WATER=1]Flammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor Pressure17.5 mmHg [@ 68 °F]Vapor Density1.10 [Ref Std: AIR=1]Density1.1 g/mlSpecific Gravity1.1 [Ref Std: WATER=1]Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]Molecular weightNo Data AvailableVOC Less H2O & Exempt Solvents<=20 g/l [Test Method: calculated SCAQMD rule 443.1	рН	8.4 - 9
Flash PointNo flash pointEvaporation rate1 [Ref Std: WATER=1]Flammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor Pressure17.5 mmHg [@ 68 °F]Vapor Density1.10 [Ref Std: AIR=1]Density1.1 g/mlSpecific Gravity1.1 [Ref Std: WATER=1]Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]Molecular weightNo Data AvailableVOC Less H2O & Exempt Solvents<=20 g/l [Test Method: calculated SCAQMD rule 443.1]	Melting point	Not Applicable
Evaporation rate1[Ref Std: WATER=1]Flammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor Pressure17.5 mmHg [@ 68 °F]Vapor Density1.10Density1.10Specific Gravity1.1 [Ref Std: AIR=1]Solubility in WaterModerateSolubility - non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]No Data AvailableNo Data AvailableViscos H2O & Exempt Solvents<=20 g/l [Test Method: calculated SCAQMD rule 443.1]		>=215°F
Flammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor Pressure17.5 mmHg [@ 68 °F]Vapor Density1.10 [Ref Std: AIR=1]Density1.1 g/mlSpecific Gravity1.1 [Ref Std: WATER=1]Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Flash Point	No flash point
Flammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor Pressure17.5 mmHg [@ 68 °F]Vapor Density1.10 [Ref Std: AIR=1]Density1.1 g/mlSpecific Gravity1.1 [Ref Std: WATER=1]Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Evaporation rate	1 [<i>Ref Std:</i> WATER=1]
Flammable Limits(UEL)Not ApplicableVapor Pressure17.5 mmHg [@ 68 °F]Vapor Density1.10 [Ref Std: AIR=1]Density1.1 g/mlSpecific Gravity1.1 [Ref Std: WATER=1]Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNot ApplicableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]Molecular weightNo Data AvailableVOC Less H2O & Exempt Solvents<=20 g/l [Test Method: calculated SCAQMD rule 443.1]	Flammability (solid, gas)	Not Applicable
Vapor Pressure17.5 mmHg [@. 68 °F]Vapor Density1.10 [Ref Std: AIR=1]Density1.1 g/mlSpecific Gravity1.1 [Ref Std: WATER=1]Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosity15 - 40 centipoise [@. 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Flammable Limits(LEL)	Not Applicable
Vapor Density1.10[Ref Std: AIR=1]Density1.1 g/mlSpecific Gravity1.1[Ref Std: WATER=1]Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Flammable Limits(UEL)	Not Applicable
Vapor Density1.10[Ref Std: AIR=1]Density1.1 g/mlSpecific Gravity1.1[Ref Std: WATER=1]Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Vapor Pressure	$17.5 \text{ mmHg} [@, 68 ^{\circ}\text{F}]$
Specific Gravity1.1 [Ref Std: WATER=1]Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]		
Solubility in WaterModerateSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Density	1.1 g/ml
Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Specific Gravity	1.1 [<i>Ref Std:</i> WATER=1]
Partition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNot Data AvailableViscosity15 - 40 centipoise [@. 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Solubility in Water	Moderate
Partition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Solubility- non-water	No Data Available
Decomposition temperatureNo Data AvailableViscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]		No Data Available
Viscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Autoignition temperature	Not Applicable
Viscosity15 - 40 centipoise [@ 73.4 °F]Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]	Decomposition temperature	No Data Available
Hazardous Air Pollutants<=0 % weight [Test Method: Calculated]		15 - 40 centipoise [@ 73.4 °F]
VOC Less H2O & Exempt Solvents <=20 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1	Hazardous Air Pollutants	<=0 % weight [<i>Test Method:</i> Calculated]
	Molecular weight	No Data Available
Solids Content 40 - 50 %	VOC Less H2O & Exempt Solvents	<=20 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1
	Solids Content	40 - 50 %

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

Condition

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Polychloroprene	Dermal		LD50 estimated to be > 5,000 mg/kg
Polychloroprene	Ingestion	Rat	LD50 > 20,000 mg/kg
Zinc Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc Oxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Polychloroprene	Human	No significant irritation
Zinc Oxide	Human	No significant irritation
	and	
	animal	

Serious Eye Damage/Irritation

Name	Species	Value
Polychloroprene	Professio nal judgeme nt	No significant irritation
Zine Oxide	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
Zinc Oxide	Guinea pig	Some positive data exist, but the data are not sufficient for classification

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Zinc Oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc Oxide	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Zinc Oxide	Ingestion	Some positive reproductive/developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Zinc Oxide	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	10 days
Zinc Oxide	Ingestion	endocrine system	Some positive data exist, but the	Other	NOAEL 500	6 months

3M[™] Fastbond[™] Foam Adhesive 100 11/03/16

	hematopoietic system kidney and/or bladder	data are not sufficient for classification		mg/kg/day	
--	--	--	--	-----------	--

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No	Pressure Hazard - No	Reactivity Hazard - No	Immediate Hazard - No	Delayed Hazard -
Yes				

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	08-3432-5	Version Number:	24.01
Issue Date:	11/03/16	Supercedes Date:	05/08/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com